

Stekerbare centraaldozen



CW75-DE5, dimmer enkelpolige schakeling

- Applicable in hollow ceiling constructions.
- Suitable for rachel ceilings and metal stud ceilings.
- Attema connectoren Installeren 2.0
- Voorzien van 1x voeding (male rood), 1x dimmer (female blauw), 1x lichtpunt aansluiting op centraaldoosdekseel

Article no:	AT8404-5
EAN:	8712259552804
Amount Packaging	1 st.
Ø circular saw	76 mm
Outer size	79 mm
Fireproof	No
Number of Outlets	5
Mounting method	Hollow ceiling
Degree of protection (IP)	-
Material	Plastic
Width	
Length	
Diameter	76 mm
Halogen free	Yes
Colour	Grey
Model	Single
Surface protection	-
Circuit integrity	None
Cover model	Mounting cover
Inner depth	77 mm
Degree of protection (NEMA)	-
Equipped with	Other
Shape	Round
Depth	79 - 79 mm
Pipe locking	Yes
Construction type	Central conduit box
Number of inlets	12
Air tight	Yes
For tube diameter	16/19 mm
Max. conductor cross section	2.5 mm ²
Inlet from the rear	No
Transparent cover	No
Cover attachment	Screwed
Sealable	No
With screening	No
Provided with revolving ring	No
Connectable	No
For number of electric fittings	
Mounting switching equipment	-
With screws	No

Housing feed-through by break-out opening	No
Housing feed-through by seal membrane	No
Housing feed-through by nozzle	No
Housing feed-through by step membrane	No
Pipe locking optional	No
Number of included spouts	
Number of poles of the clamp	
Clamp position fixed	No
Luminaire hook mounting	Yes
Nozzle	Tunnel branch pipe
With nail lugs	No
Special application	Other

Installeren 2.0 is een stekerbaar installatiesysteem gebaseerd op voorbedrade centraal- en kabeldozen in combinatie met prefab gemonteerd schakelmateriaal en een stekerbare groepenkast. Deze onderdelen worden met soepele kabels aangesloten. De installatietijd wordt daardoor sterk ingekort ten opzichte van traditioneel installeren en faalkosten worden tot een minimum beperkt.