

## Stekerbare kabeldozen



### AKW-S2, serieschakeling

- Equipped with 1x power supply (male black), 1x switch (female brown), 2x light point connection (female white)
- Attema connectoren Installeren 2.0

|                              |                        |
|------------------------------|------------------------|
| <b>Article no:</b>           | <b>AT8505-2</b>        |
| EAN:                         | 8712259554006          |
| Amount Packaging             | 1 st.                  |
| Switched                     | Series switch          |
| Number of Outlets            | 2                      |
| Rated insulation voltage Ui  | 690 V                  |
| Mounting method              | Wall-/ceiling mounting |
| Degree of protection (IP)    | IP20                   |
| Material                     | Plastic                |
| Width                        | 95 mm                  |
| Length                       | 120 mm                 |
| Diameter                     |                        |
| Halogen free                 | Yes                    |
| Colour                       | Grey                   |
| Surface protection           | -                      |
| Explosion-tested version     | No                     |
| For Ex-zone gas              | None                   |
| For Ex-Zone dust             | None                   |
| Operating temperature        | -40 - 70 °C            |
| Circuit integrity            | None                   |
| Depth                        | 60 mm                  |
| Cover model                  | Blind cover            |
| Degree of protection (NEMA)  | -                      |
| Equipped with                | Mounting plate         |
| Shape                        | Rectangular            |
| Tackable                     | No                     |
| Number of inlets             | 10                     |
| For tube diameter            | -                      |
| Max. conductor cross section | 2.5 mm <sup>2</sup>    |
| Mounting in the soil         | No                     |
| Mounting under water         | No                     |
| Inlet from the rear          | No                     |
| Type of housing feed-through | Other                  |
| Transparent cover            | No                     |
| Cover attachment             | Snapped on             |
| Castable                     | No                     |
| With casting compound        | Yes                    |
| Sealable                     | No                     |
| With screening               | No                     |
| Weatherproof                 | No                     |

Installeren 2.0 is een stekerbaar installatiesysteem gebaseerd op voorbedrade centraal- en kabeldozen in combinatie met prefab gemonteerd schakelmateriaal en een stekerbare groepenkast. Deze onderdelen worden met soepele kabels aangesloten. De installatietijd wordt daardoor sterk bekort ten opzichte van traditioneel installeren, en faalkosten worden tot een minimum beperkt.