


Stekerbare kabeldozen



AKW-DET5, dimmer enkelpolige schakeling 2-voudig

- Equipped with 1x power supply (male red), 1x dimmer (female blue), 2x light point connection (female white).
- Attema connectoren Installeren 2.0

Article no:	AT8519-5
EAN:	8712259575209
Amount Packaging	1 st.
Rated insulation voltage Ui	690 V
Mounting method	Wall-/ceiling mounting
Degree of protection (IP)	IP20
Material	Plastic
Width	95 mm
Length	120 mm
Diameter	
Halogen free	Yes
Colour	Grey
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-40 - 69 °C
Circuit integrity	None
Depth	80 mm
Cover model	Blind cover
Equipped with	Mounting plate
Shape	Rectangular
Tackable	No
Number of inlets	10
Max. conductor cross section	2.5 mm ²
Mounting in the soil	No
Mounting under water	No
Inlet from the rear	No
Type of housing feed-through	Other
Transparent cover	No
Cover attachment	Snapped on
Castable	No
With casting compound	No
Sealable	No
With screening	No
Weatherproof	No

Installeren 2.0 is een stekbaar installatiesysteem gebaseerd op voorbedrade centraal- en kabeldozen in combinatie met prefab gemonteerd schakelmateriaal en een stekerbare groepenkast. Deze onderdelen worden met soepele kabels aangesloten. De installatietijd wordt daardoor sterk bekort ten opzichte van traditioneel installeren, en faalkosten worden tot een minimum beperkt.