

## Empty boxes and parts

**M32 wartel met contraamoer**

- For entering cables from below.
- Suitable for mounting in the cable input plate (art. no. AT90054).

<b>Article no:</b>	<b>AT90055</b>
EAN:	8712259535920
Degree of protection (IP)	IP68
Material	Plastic
Halogen free	Yes
Colour	Grey
RAL-number	7035
Model	Straight
Material quality	Polyamide (PA)
Surface protection	Untreated
With strain relief	Yes
Thread type	Metric
Nominal thread size metric/PG	32
Nominal thread size inch/gas pipe thread	-
Pitch thread	1.5 mm
Glass-fibre reinforced	No
Shock resistant	No
Explosion-tested version	No
For Ex-zone gas	None
For Ex-Zone dust	None
Operating temperature	-30 - 100 °C
Thread length	10 mm
EMC-version	No
Wrench width	42 mm
Suitable for cable diameter	17 - 25 mm
Hexagon angular dimension	
Bend radius protection/trumpet flare	No
With locknut	Yes
Snapping in opening	No
Multi seal area	No
Flat cable coupling	No
Type of sealing	Diaphragm
Separable screw gland	No
For armoured cable	No
Screened	No
Dispatch	25

The new generation of Click-mate NXT distribution boxes is available in various versions: The compact S distribution box with 12 modules, the familiar M distribution box with space for 2 x 12 modules and the innovative L distribution cabinet with 2 x 18 modules; the solution for the energy transition and extensive 3-phase installations. The distribution boxes are also completely modular and can easily be installed next to or underneath each other.