


## K25/P25 Flat tube system Raceways

### K25 Trunking base + cover, 4 m white (RAL 9010)

- Mount using BC25 wall clips (art. no. AT5600).
- Stackable.
- Internal dimensions: 23 x 8 mm



<b>Article no:</b>	<b>AT9068</b>
EAN:	8712259011905
Colour	-
Amount Packaging	25 lgt. x 4 m
Degree of protection (IP)	-
Material	Plastic
Height	13 mm
Width	25 mm
Length	4000 mm
Halogen free	No
Useful cross section	154 mm <sup>2</sup>
Type of fastening	Snapper mounting
RAL-number	9010
Material quality	Polyvinyl chloride (PVC)
Surface protection	Untreated
Transparent	No
Anti-bacterial treatment	No
Impact strength	-
Cover model	Loose
Suitable for circuit integrity	Yes
Number of permanent partitions	
Number of plug-in partitions	
With cable fixing clip	Yes
With protective foil	No
With duct connector	Yes
Delivery on roll	No
Pre-stamping	No

Z25 and F25 are the surface-mounted systems for installation-friendly data cabling. Thanks to the smart accessories, the entire contents of the tubes can be used for data cables up to Ø 10 mm. A minimum bending radius of 25 mm is assured with all accessories. Thanks to clickers and target plates, you can install the system quickly and easily. Due to the special lid, F25 is extremely suitable for public spaces such as Fiber to the Home projects in high-rise buildings and stairwells. Because the lid is difficult to disassemble, unauthorized opening is prevented and the risk of disruptions to telephone, internet and television traffic is reduced.