

## Distribution boards with earth leakage circuit breakers



## NXT S1-4Q groepenkast

|  |  |
|--|--|
| <b>Article no:</b>                           | <b>AT91016</b>                             |
| EAN:   | 8712259533865                              |
| Width  | 220 mm                                     |
| Height                                       | 250 mm                                     |
| Phases                                       | 1-phase wired                              |
| Groups                                       | 4  |
| Main switch                                  | None                                       |
| Rated current                                | 40 A                                       |
| Quantity and type of FI/LS switch            | 4 x RCBO 1P+N, 16A, B-char. 30mA<br>       |
| Mounting method                              | Surface mounted (plaster)                  |
| Degree of protection (IP)                    | IP20                                       |
| Width in number of modular spacings          | 12   |
| Depth  | 110 mm                                     |
| Extension possible                           | Yes  |
| Housing material                             | Plastic                                    |
| Number of phases                             | 1  |
| Lockable                                     | Yes  |
| Over voltage protection                      | No   |
| Number of earth leakage switches 30 mA       |  |
| Number of earth leakage switches 300 mA      |  |
| With transparent cover                       | No   |
| Protection                                   | Miniature- / earth leakage circuit breaker |
| Total number of groups                       | 4  |
| Number of direct groups                      |  |
| Number of light groups                       | 4  |
| Number of groups behind earth leakage switch |  |
| Number of earth leakage circuit breakers     | 4  |
| Number of arc fault detection devices AFDD   |  |
| Protection main switch                       | No   |
| Number of poles main switch                  |  |
| Main switch rated current                    |  |
| Protection incoming RCD                      | No   |
| Protection high integrity                    | No   |
| Protection split load                        | No   |
| Protection dual RCD                          | No   |
| Number of outgoing ways                      | 18   |
| Suitable for data                            | No   |
| Cooker group                                 | None                                       |
| Cooker group suitable as power current group | No   |
| With socket outlet                           | No   |
| With bell transformer                        | No   |
| Type of over voltage protection device       | -  |
| With meter                                   | No   |
| Built-in depth                               | 55 mm                                      |

Click-mate NXT distribution boxes equipped with earth leakage circuit breakers 1P+N, 16A, 30mA.