


## Main switch boxes



## NXT HS-H2 hoofdschakelaarkast

<b>Article no:</b>	<b>AT91018</b>
EAN:	8712259533889
Width	220 mm
Height	190 mm
Rated current	40 A
Phases	1-phase wired
Main switch	40 A
Connecting wires	Yes
Quantity and type of FI/LS switch	
Mounting method	Cabinet mounted/skeleton unit
Degree of protection (IP)	IP20
Width in number of modular spacings	12
Depth	110 mm
Extension possible	Yes
Housing material	Plastic
Number of phases	1
Lockable	Yes
Over voltage protection	No
Number of earth leakage switches 30 mA	
Number of earth leakage switches 300 mA	
With transparent cover	No
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	
Number of direct groups	
Number of light groups	
Number of groups behind earth leakage switch	
Number of earth leakage circuit breakers	
Number of arc fault detection devices AFDD	
Protection main switch	No
Number of poles main switch	2
Main switch rated current	40 A
Protection incoming RCD	No
Protection high integrity	No
Protection split load	No
Protection dual RCD	No
Number of outgoing ways	
Suitable for data	No
Cooker group	None
Cooker group suitable as power current group	No
With socket outlet	No
With bell transformer	No
Type of over voltage protection device	-
With meter	No
Built-in depth	55 - 55 mm

Main switch boxes without output bridge. Easy to install under the Click-mate NXT Distribution boxes or expansion boxes.