

XL 115 S Extension boxes



CM-XL 115-QM1 S Uitbreidingskast

Article no:	AT91420
EAN:	8712259544786
Width	115 mm
Height	220 mm
Colour	Black
Phases	1-phase wired
Groups	1
Main switch	None
kWh-meter	kWh-meter 1-phase MID
Rated current	32 A
Quantity and type of F/LS switch	RCBO 1P+N, 16A, B-char. 30mA
Mounting method	Surface mounted (plaster)
Degree of protection (IP)	IP20
Width in number of modular spacings	6
Depth	95 mm
Extension possible	Yes
Housing material	Plastic
Number of phases	1
Lockable	Yes
Over voltage protection	No
Number of earth leakage switches 30 mA	
Number of earth leakage switches 300 mA	
With transparent cover	No
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	1
Number of direct groups	
Number of light groups	1
Number of groups behind earth leakage switch	
Number of earth leakage circuit breakers	1
Number of arc fault detection devices AFDD	
Protection main switch	Yes
Number of poles main switch	
Main switch rated current	
Protection incoming RCD	Yes
Protection high integrity	Yes
Protection split load	Yes
Protection dual RCD	Yes
Number of outgoing ways	3
Suitable for data	Yes
Cooker group	-
Cooker group suitable as power current group	Yes
With socket outlet	No
With bell transformer	No
Type of over voltage protection device	-

With meter	Yes
------------	-----

Compact Click-mate XL 115 S cabinets. Also suitable as an extension to existing Click-mate XL-plus installations.