Distribution boxes with earth leakage switches and circuit breakers



NXT M-22/21/00-H2 groepenkast

EAN: 8712259533933 Width 220 mm Height 390 mm Number of groups (blue) 2 Number of groups (grey) 1 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 3 Main switch 40 A Rated current 40 A Rated current 40 A Quantity and type of FVLS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 30 mA 2 With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of light groups 3 Number of light groups 3 Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of poles main switch No Number of poles main switch No Number of poles main switch No Protection incoming RCD No Protection dual RCD No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group With socket outlet With belt transformer No	Article no:	AT91501
Height 390 mm Number of groups (blue) 2 Number of groups (grey) 1 Number of groups (grey) 1 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 3 Main switch 40 A Rated current 40 A Quantity and type of FI/LS switch Mounting method 5 Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups Number of groups behind earth leakage switch Number of groups 8 Number of groups 8 Number of groups behind earth leakage switch Number of poles main switch No Number of arc fault detection devices AFDD Protection main switch No No Protection nigh integrity No Protection split load No Protection group suitable as power current group With socket outlet No	EAN:	8712259533933
Number of groups (blue) 2 Number of groups (grey) 1 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 3 Main switch 40 A Rated current 40 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 30 mA 2 Vith transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of direct groups Number of ignets groups 3 Number of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection split load No Protection group suitable as power current group With socket outlet	Width	220 mm
Number of groups (grey) Number of earth fault switches 2P Phases 1-phase wired Groups 3 Main switch 40 A Rated current 40 A Quantity and type of FVLS switch Mounting method Degree of protection (IP) Width in number of modular spacings Extension possible Yes Housing material Number of phases 1 Lockable Ves Over voltage protection No Number of earth leakage switches 30 mA With transparent cover Protection Total number of direct groups Number of groups behind earth leakage switch Number of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch No No Protection incoming RCD Protection numbin integrity No Protection lual RCD No No No No No No Protection split load Protection split load No Protection split lo	Height	390 mm
Number of earth fault switches 2P Phases 1-phase wired Groups 3 Main switch 40 A Rated current 40 A Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings 24 Depth 110 mm Extension possible Housing material Number of phases 1 Lockable Ver voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Number of gight groups Number of groups Number of groups S Number of groups Sehind earth leakage switch Number of earth leakage circuit breaker Number of arc fault detection devices AFDD Protection main switch Number of position No Number of protection Aviance No Protection Miniature- / earth leakage circuit breaker Number of groups Number of groups Number of groups A Number of groups Number of groups A Number of phases Number of arc fault detection devices AFDD Protection main switch Number of phases No Protection incoming RCD No Protection incoming RCD No Protection split load No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group None Cooker group suitable as power current group With socket outlet	Number of groups (blue)	2
Phases 1-phase wired Groups 3 Main switch 40 A Rated current 40 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 30 mA 2 Number of earth leakage switches 30 mA 3 Number of direct groups No Protection Miniature- / earth leakage circuit breaker 3 Number of groups a 3 Number of groups behind earth leakage switch switch No Number of earth leakage circuit breaker 3 Number of groups behind earth leakage switch No Nomber of arc fault detection devices AFDD Protection main switch No Number of poss main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection by No Protection dal RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet No	Number of groups (grey)	1
Groups 3 Main switch 40 A Rated current 40 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of light groups 3 Number of direct groups Number of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection Mone APD Protection No Number of ploes main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection split load No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet	Number of earth fault switches 2P	2
Main switch 40 A Rated current 40 A Rated current 40 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of direct groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection split load No Protection split load No Protection group suitable as power current group With socket outlet No	Phases	1-phase wired
Rated current Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings Depth Depth Depth Depth Depth Destresion possible Extension possible Housing material Number of phases Dever voltage protection No Number of earth leakage switches 30 mA Number of earth leakage switches 30 mA With transparent cover Protection No Number of direct groups Number of light groups Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Number of poles main switch No Protection incoming RCD No Protection high integrity No Protection split load No Protection split load No Protection data Cooker group suitable as power current group With socket outlet No	Groups	3
Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of direct groups Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of poles main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet	Main switch	40 A
Mounting method Degree of protection (IP) Width in number of modular spacings Depth 110 mm Extension possible Yes Housing material Number of phases 1 Lockable Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Total number of groups Number of direct groups Number of groups behind earth leakage switch Number of earth leakage circuit breaker Total number of groups Number of Jight groups Number of Jight groups Number of Jight groups Number of poles main switch Number of earth leakage circuit breakers Number of poles main switch No Number of poles main switch No Number of poles main switch No Protection incoming RCD No Protection high integrity No Protection dual RCD No No Number of outgoing ways Suitable for data No Cooker group suitable as power current group With socket outlet No	Rated current	40 A
Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 1110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of poles main switch No No Protection No No Protection No N	Quantity and type of FI/LS switch	
Width in number of modular spacings Depth Depth Extension possible Housing material Number of phases Lockable Over voltage protection Number of earth leakage switches 30 mA Vith transparent cover Protection Number of groups Number of direct groups Number of light groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of proups behind earth leakage switch Number of earth leakage circuit breakers Number of poles main switch No No Protection main switch No No Protection high integrity Protection split load Protection dual RCD No No No No No No No No No N	Mounting method	Surface mounted (plaster)
Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of direct groups Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of or carth leakage circuit breakers Number of poles main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet	Degree of protection (IP)	IP20
Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of direct groups Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet	Width in number of modular spacings	24
Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of direct groups Number of groups Behind earth leakage switch Number of groups behind earth leakage switch Number of acr fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet No	Depth	110 mm
Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of direct groups Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet No	Extension possible	Yes
Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of direct groups Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group With socket outlet No	Housing material	Plastic
Over voltage protection No Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of direct groups Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group With socket outlet	Number of phases	1
Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover Protection No Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Vain switch rated current 40 A Protection incoming RCD Protection high integrity No Protection dual RCD No No No No No No No No No N	Lockable	Yes
Number of earth leakage switches 300 mA With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Protection incoming RCD No Protection high integrity No Protection dual RCD Number of outgoing ways Suitable for data Cooker group With socket outlet No Miniature- / earth leakage circuit breaker No No No No No No No No No N	Over voltage protection	No
With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of light groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Vain switch rated current Valo A Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways No Suitable for data Cooker group Cooker group suitable as power current group With socket outlet No Number of earth leakage circuit breakers No Mo No	Number of earth leakage switches 30 mA	2
Protection Miniature- / earth leakage circuit breaker Total number of groups 3 Number of direct groups Number of light groups 3 Number of groups behind earth leakage 3 switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group No With socket outlet No	Number of earth leakage switches 300 mA	
Total number of groups Number of direct groups Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group No With socket outlet	With transparent cover	No
Number of direct groups Number of light groups 3 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group With socket outlet	Protection	Miniature- / earth leakage circuit breaker
Number of light groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group None Cooker group suitable as power current group With socket outlet	Total number of groups	3
Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group No With socket outlet No No No No No No No No No N	Number of direct groups	
switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Alian switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways Suitable for data Cooker group No With socket outlet No No No No No No No No No N	Number of light groups	3
Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No With socket outlet No		3
Protection main switch Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group None Cooker group suitable as power current group With socket outlet No	Number of earth leakage circuit breakers	
Number of poles main switch Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group Cooker group suitable as power current group With socket outlet No No 2 Mo No No No No No No No No No	Number of arc fault detection devices AFDD	
Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways Suitable for data Cooker group Cooker group suitable as power current group With socket outlet No	Protection main switch	No
Protection incoming RCD Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group Cooker group suitable as power current group With socket outlet No	Number of poles main switch	2
Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group Cooker group suitable as power current group With socket outlet No	Main switch rated current	40 A
Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No With socket outlet No	Protection incoming RCD	No
Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No With socket outlet No	Protection high integrity	No
Number of outgoing ways Suitable for data Cooker group None Cooker group suitable as power current group With socket outlet No	Protection split load	No
Suitable for data Cooker group Cooker group suitable as power current group With socket outlet No	Protection dual RCD	No
Cooker group None Cooker group suitable as power current group No With socket outlet No	Number of outgoing ways	18
Cooker group suitable as power current group No With socket outlet No	Suitable for data	No
With socket outlet No	Cooker group	None
	Cooker group suitable as power current group	No
With bell transformer No	With socket outlet	No
	With bell transformer	No



Type of over voltage protection device	-
With meter	No
Built-in depth	55 mm

The new generation of Click-mate NXT distribution boxes is available in various editions: The compact S distribution cabinet with 12 modules, the familiar M distribution cabinet with space for 2 x 12 modules and the innovative L distribution cabinet with 2 x 18 modules; the solution for the energy transition and extensive 3-phase installations. The distribution boxes are also completely modular and can easily be installed next to or underneath each other. The distribution boxes in the extensive range are equipped with earth leakage circuit breakers (2P, 40A, 30mA) and circuit breakers (1P+N, 16A, B-characteristic) and are optionally available with a stove group and/or bell transformer.

