Extension boxes



NXT M1-22/22/00 groepenkast

EAN: 8712259533957 Width 220 mm Height 390 mm Number of groups (blue) 2 Number of groups (grey) 2 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Main switch None Rated current 40 A Quantity and type of FI/LS switch Mounting method Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA 2 With transparent cover No Nounber of flight groups 4 Number of groups behind earth leakage 4 Number of light groups 4 Number of poles main switch No	Article no:	AT91503
Height 390 mm Number of groups (blue) 2 Number of groups (grey) 2 Number of groups (grey) 2 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Main switch None Rated current 40 A Quantity and type of FVLS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of dight groups 4 Number of eight groups 4 Number of earth leakage circuit breaker Number of groups behind earth leakage switch Number of earth leakage circuit breaker Number of or fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection high integrity No Protection dual RCD No Nome Ooker group Suitable as power current group With socket outlet No With socket outlet No	EAN:	8712259533957
Number of groups (blue) 2 Number of groups (grey) 2 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Main switch None Rated current 40 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 300 mA With transparent cover No Protection Total number of groups 4 Number of direct groups Number of direct groups Number of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection high integrity No Protection split load No Protection polit load No Protection plit load No Protection plit load No Protection split load No Protection group Suitable as power current group With socket outlet	Width	220 mm
Number of groups (grey) Number of earth fault switches 2P Phases 1-phase wired Groups 4 Main switch None Rated current 40 A Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Degree of protection (IP) Power of phases 110 mm Extension possible Yes Housing material Number of phases 1 Lockable Vers Over voltage protection No Number of earth leakage switches 30 mA With transparent cover Protection Vimber of direct groups Number of groups A Number of groups Number of groups Number of groups Number of groups Number of earth leakage circuit breaker Number of protection being the direct groups Number of protection being the direct groups Number of protection No Number of light groups Number of protection No Number of protection No Number of protection No No Number of protection No No No No Protection No	Height	390 mm
Number of earth fault switches 2P Phases 1-phase wired Groups 4 Main switch None Rated current 40 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Housing material Number of phases 1 Lockable Ves Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Number of groups A Number of groups A Number of light groups A Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of light groups A Number of light groups No No Protection No	Number of groups (blue)	2
Phases 1-phase wired Groups 4 Main switch None Rated current 40 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 30 mA 4 With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No None Cooker group Suitable as power current group With socket outlet No	Number of groups (grey)	2
Groups 4 Main switch None Rated current 40 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups 4 Number of arc fault detection devices AFDD Protection main switch Main switch rated current Protection nicoming RCD No Protection dugoing ways 18 Number of outgoing ways 18 Suitable for data No Nome Cooker group suitable as power current group With socket outlet No	Number of earth fault switches 2P	2
Main switch Rated current 40 A Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings Depth 110 mm Extension possible Yes Housing material Number of phases 1 Lockable Ves Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Total number of groups Number of groups Number of groups Number of groups A Number of groups A Number of arc fault detection devices AFDD Protection main switch Main switch rated current Protection ligh integrity No Protection dup integrity No Protection number of poles main switch Main switch rated current Protection incoming RCD No No Number of outgoing ways 18 Suitable for data Cooker group None Cooker group suitable as power current group With socket outlet No With socket outlet	Phases	1-phase wired
Rated current Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings Depth 110 mm Extension possible Housing material Number of phases 1 Lockable Ves Over voltage protection No Number of earth leakage switches 30 mA With transparent cover Protection Total number of groups Number of direct groups Number of earth leakage circuit breaker Number of earth leakage circuit breakers Number of plight groups A Number of earth leakage circuit breakers Number of propes Number of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dala RCD No Number of outgoing ways Suitable for data Cooker group suitable as power current group With socket outlet No With socket outlet	Groups	4
Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 1110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breaker Number of groups behind earth leakage 4 Number of protection Aumber of groups No Number of protection Aumber of groups No Number of protection behind earth leakage Aumber of groups behind earth leakage Aumber of groups behind earth leakage Aumber of earth leakage circuit breakers Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of poles main switch No Number of poles main switch No Number of poles main switch No Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet No	Main switch	None
Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of poles main switch No Number of poles main switch No Number of poles main switch No Protection nicoming RCD No Protection tolal RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group With socket outlet No	Rated current	40 A
Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Main switch rated current Protection incoming RCD No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet No	Quantity and type of FI/LS switch	
Width in number of modular spacings Depth 1110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of or cfault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet No	Mounting method	Surface mounted (plaster)
Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of oart fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet No	Degree of protection (IP)	IP20
Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of acr fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group With socket outlet No	Width in number of modular spacings	24
Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of groups 4 Number of groups behind earth leakage switch Number of acr fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet No	Depth	110 mm
Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet No	Extension possible	Yes
Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Switable as power current group With socket outlet No	Housing material	Plastic
Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of arth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group With socket outlet No	Number of phases	1
Number of earth leakage switches 30 mA With transparent cover Protection No Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group With socket outlet No No No No No No No No No N	Lockable	Yes
Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group With socket outlet No Miniature- / earth leakage circuit breaker A No	Over voltage protection	No
With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Aumber of direct groups Number of light groups Aumber of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection dual RCD No Number of outgoing ways No Suitable for data Cooker group Vith socket outlet Number of groups No	Number of earth leakage switches 30 mA	2
Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group No With socket outlet No	Number of earth leakage switches 300 mA	
Total number of groups Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD No No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group With socket outlet	With transparent cover	No
Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Cooker group suitable as power current group With socket outlet Number of light groups 4 No	Protection	Miniature- / earth leakage circuit breaker
Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No With socket outlet No	Total number of groups	4
Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group No With socket outlet A A	Number of direct groups	
switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group With socket outlet No	Number of light groups	4
Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group Cooker group suitable as power current group With socket outlet No		4
Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group None Cooker group suitable as power current group With socket outlet No	Number of earth leakage circuit breakers	
Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No With socket outlet No	Number of arc fault detection devices AFDD	
Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No With socket outlet No	Protection main switch	No
Protection incoming RCD Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group Cooker group suitable as power current group With socket outlet No	Number of poles main switch	
Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group Cooker group suitable as power current group With socket outlet No	Main switch rated current	
Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No With socket outlet No	Protection incoming RCD	No
Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No With socket outlet No	Protection high integrity	No
Number of outgoing ways Suitable for data Cooker group None Cooker group suitable as power current group With socket outlet No	Protection split load	No
Suitable for data Cooker group Cooker group suitable as power current group With socket outlet No	Protection dual RCD	No
Cooker group None Cooker group suitable as power current group No With socket outlet No	Number of outgoing ways	18
Cooker group suitable as power current group No With socket outlet No	Suitable for data	No
With socket outlet No	Cooker group	None
	Cooker group suitable as power current group	No
With bell transformer No	With socket outlet	No
	With bell transformer	No



Type of over voltage protection device	-
With meter	No
Built-in depth	55 mm

Click-mate NXT distribution boxes without main switch. To expand existing installations.

