Distribution boxes with earth leakage switches and circuit breakers



NXT M-22/22/00-T/H2 groepenkast

EAN: 8712259533988 Width 220 mm Height 390 mm Number of groups (blue) 2 Number of groups (grey) 2 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Bell transformer 1 Main switch 40 A Rated current 40 A Quantity and type of FI/LS switch Wounting method Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 nm Extension possible Yes Extension possible Yes Vova voltage protection No Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Vith transparent cover No Protection Miniature- / earth leakage circuit breaker Number of groups 4	Article no:	AT91506
Height 390 mm Number of groups (blue) 2 Number of groups (grey) 2 Number of groups (grey) 2 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Bell transformer 1 Main switch 40 A Rated current 40 A Quantity and type of FVLS switch Mounting method 5urface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection Number of earth leakage switches 30 mA With transparent cover No Protection 4 Number of direct groups Number of direct groups Number of direct groups Number of groups behind earth leakage switch Number of earth leakage circuit breaker Number of earth leakage circuit breakers Number of of orthe table the switch Number of ore fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch and No Protection high integrity No Protection high integrity No Protection split load No Protection dual RCD No Number of outagoing ways 18 Suitable for data No Cooker group suitable as power current group	EAN:	8712259533988
Number of groups (blue) 2 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Bell transformer 1 Main switch 40 A Rated current 40 A Quantity and type of FI/LS switch Surface mounted (plaster) Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups 4 Number of eight groups 4 Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of poles main switch	Width	220 mm
Number of groups (blue) 2 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Bell transformer 1 Main switch 40 A Rated current 40 A Quantity and type of FI/LS switch Surface mounted (plaster) Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups 4 Number of eight groups 4 Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of poles main switch	Height	390 mm
Number of groups (grey) 2 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Bell transformer 1 Main switch 40 A Rated current 40 A Quantity and type of FI/LS switch Surface mounted (plaster) Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Vith transparent cover No Protection Miniature- / earth leakage circuit breaker Number of groups 4 Number of groups behind earth leakage switches 30 mA 4 Number of groups behind earth leakage switches 4FDD Yes Number of poles main switch No Number of poles main switch <td></td> <td>2</td>		2
Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Bell transformer 1 Main switch 40 A Rated current 40 A Quantity and type of FI/LS switch Width in puber of protection (IP) Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Vith transparent cover No Number of earth leakage switches 30 mA Yes Vith transparent cover No Number of groups 4 Number of groups behind earth leakage 4 Number of groups behind earth leakage 4 Number of act all detection devices AFDD No Protection main switch No	- 1	2
Groups4Bell transformer1Main switch40 ARated current40 AQuantity and type of FI/LS switchSurface mounted (plaster)Mounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2With transparent coverNoProtectionMiniature-/ earth leakage circuit breakerTotal number of groups4Number of direct groups4Number of groups behind earth leakage switch4Number of groups behind earth leakage switch4Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switchNoNumber of poles main switch2Main switch rated current40 AProtection incoming RCDNoProtection fligh integrityNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker group suitable as power current groupNo		2
Groups4Bell transformer1Main switch40 ARated current40 AQuantity and type of FI/LS switchSurface mounted (plaster)Mounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2With transparent coverNoProtectionMiniature-/ earth leakage circuit breakerTotal number of groups4Number of direct groups4Number of groups behind earth leakage switch4Number of groups behind earth leakage switch4Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switchNoNumber of poles main switch2Main switch rated current40 AProtection incoming RCDNoProtection fligh integrityNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker group suitable as power current groupNo	Phases	1-phase wired
Main switch 40 A Rated current 40 A Rated current 40 A Quantity and type of FI/LS switch Mounting method 5urface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 1110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups 4 Number of earth leakage circuit breaker Number of argoups behind earth leakage 4 switch Number of earth leakage circuit breaker Number of ploes main switch No Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch No Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group None	Groups	4
Rated current Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) P20 Width in number of modular spacings Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 1 Lockable Ver voltage protection No Number of earth leakage switches 30 mA With transparent cover Protection Total number of groups Number of direct groups Number of groups behind earth leakage switch Number of earth leakage circuit breaker Number of propus behind earth leakage Number of propus behind earth leakage Switch Number of earth leakage circuit breaker Total number of groups behind earth leakage Switch Number of groups behind earth leakage Switch Number of poles main switch Number of earth leakage circuit breakers Number of poles main switch No Protection incoming RCD No Protection dual RCD No No Protection dual RCD No No No Cooker group suitable as power current group No Cooker group suitable as power current group No No Cooker group suitable as power current group No		1
Quantity and type of FI/LS switchSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2Number of earth leakage switches 300 mA2With transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups4Number of light groups4Number of groups behind earth leakage switch4Number of earth leakage circuit breakers4Number of earth leakage circuit breakers4Number of poles main switchNoNumber of poles main switch2Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker group suitable as power current groupNo	Main switch	40 A
Mounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2With transparent coverNoTotal number of groups4Number of direct groups4Number of light groups4Number of groups behind earth leakage switch4Number of earth leakage circuit breakers4Number of earth leakage circuit breakers4Number of poles main switchNoNumber of poles main switchNoNumber of poles main switch2Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection high integrityNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Rated current	40 A
Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2With transparent coverNoTotal number of groups4Number of direct groups4Number of groups behind earth leakage switch4Number of earth leakage circuit breakers4Number of arc fault detection devices AFDDNoProtection main switch2Main switch rated current40 ANumber of poles main switch2Main switch rated current40 AProtection high integrityNoProtection split loadNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNone	Quantity and type of FI/LS switch	
Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2Number of earth leakage switches 300 mAWith transparent coverProtectionMiniature- / earth leakage circuit breakerTotal number of groups4Number of direct groups4Number of groups behind earth leakage switch4Number of earth leakage circuit breakers4Number of earth leakage circuit breakers4Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switchNoNumber of poles main switchNoProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNone		Surface mounted (plaster)
Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2Number of earth leakage switches 300 mAWith transparent coverProtectionMiniature- / earth leakage circuit breakerTotal number of groups4Number of direct groups4Number of groups behind earth leakage switch4Number of earth leakage circuit breakers4Number of earth leakage circuit breakers4Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switchNoNumber of poles main switchNoProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNone	Degree of protection (IP)	IP20
Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of groups behind earth leakage switch Number of proups 4 Number of groups 4 Number of groups Number of groups A Number of groups A Number of groups behind earth leakage Switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group No		24
Housing materialPlasticNumber of phases1LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups4Number of direct groups4Number of groups behind earth leakage switch4Number of earth leakage circuit breakers4Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switch2Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Depth	110 mm
Number of phases1LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups4Number of direct groups4Number of light groups4Number of groups behind earth leakage switch4Number of earth leakage circuit breakersNumber of arc fault detection devices AFDDProtection main switchNoNumber of poles main switch2Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Extension possible	Yes
LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups4Number of light groups4Number of groups behind earth leakage switch4Number of earth leakage circuit breakersNumber of arc fault detection devices AFDDProtection main switchNoNumber of poles main switch2Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Housing material	Plastic
Over voltage protectionNoNumber of earth leakage switches 30 mA2Number of earth leakage switches 300 mANoWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups4Number of direct groups4Number of groups behind earth leakage switch4Number of earth leakage circuit breakers4Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switch2Main switch rated current40 AProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Number of phases	1
Number of earth leakage switches 30 mA With transparent cover Protection Protection Miniature- / earth leakage circuit breaker Total number of groups Aumber of direct groups Number of light groups Aumber of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Ain switch rated current Ao A Protection high integrity No Protection dual RCD Number of outgoing ways 18 Suitable for data Cooker group suitable as power current group No	Lockable	Yes
Number of earth leakage switches 300 mA With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Aumber of direct groups Number of light groups Aumber of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Aumber of poles main switch Aunis switch rated current Aunis witch rated current Aunis wit	Over voltage protection	No
With transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups4Number of direct groups4Number of groups behind earth leakage switch4Number of earth leakage circuit breakers4Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switch2Main switch rated current40 AProtection incoming RCDNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Number of earth leakage switches 30 mA	2
Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group No	Number of earth leakage switches 300 mA	
Total number of groups Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Ain switch rated current Protection incoming RCD Protection high integrity No Protection split load No Protection dual RCD Number of outgoing ways No Suitable for data Cooker group No	With transparent cover	No
Number of direct groups Number of light groups A 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Adain switch rated current Protection incoming RCD Protection high integrity No Protection split load No Protection dual RCD Number of outgoing ways 18 Suitable for data Cooker group No No No No No No No No No N	Protection	Miniature- / earth leakage circuit breaker
Number of light groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Nain switch rated current Protection incoming RCD No Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways Suitable for data Cooker group No No No No No No No No No N	Total number of groups	4
Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD Number of outgoing ways 18 Suitable for data No Cooker group No	Number of direct groups	
Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Number of light groups	4
Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No		4
Protection main switch Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Number of earth leakage circuit breakers	
Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group No No No No No No No No No N	Number of arc fault detection devices AFDD	
Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Protection main switch	No
Protection incoming RCD Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Number of poles main switch	2
Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group No No No No No No No No No N	Main switch rated current	40 A
Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Protection incoming RCD	No
Protection dual RCD Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Protection high integrity	No
Number of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Protection split load	No
Suitable for data Cooker group No Cooker group suitable as power current group No	Protection dual RCD	No
Cooker group None Cooker group suitable as power current group No	Number of outgoing ways	18
Cooker group suitable as power current group No	Suitable for data	No
	Cooker group	None
With socket outlet No	Cooker group suitable as power current group	No
	With socket outlet	No



With bell transformer	Yes
Type of over voltage protection device	-
With meter	No
Built-in depth	55 mm

The new generation of Click-mate NXT distribution boxes is available in various editions: The compact S distribution cabinet with 12 modules, the familiar M distribution cabinet with space for 2 x 12 modules and the innovative L distribution cabinet with 2 x 18 modules; the solution for the energy transition and extensive 3-phase installations. The distribution boxes are also completely modular and can easily be installed next to or underneath each other. The distribution boxes in the extensive range are equipped with earth leakage circuit breakers (2P, 40A, 30mA) and circuit breakers (1P+N, 16A, B-characteristic) and are optionally available with a stove group and/or bell transformer.

