

Distribution boards with earth leakage circuit breakers



NXT M-3Q-H4 groopenkast

Article no:	AT91533
EAN:	8712259534251
Width	220 mm
Height	390 mm
Phases	3-phase wired
Groups	3
Main switch	40 A
Rated current	3 x 32 A
Quantity and type of FI/LS switch	3 x RCBO 1P+N, 16A, B-char. 30mA
Mounting method	Surface mounted (plaster)
Degree of protection (IP)	IP20
Width in number of modular spacings	24
Depth	110 mm
Extension possible	Yes
Housing material	Plastic
Number of phases	3
Lockable	Yes
Over voltage protection	No
Number of earth leakage switches 30 mA	
Number of earth leakage switches 300 mA	
With transparent cover	No
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	3
Number of direct groups	
Number of light groups	3
Number of groups behind earth leakage switch	
Number of earth leakage circuit breakers	3
Number of arc fault detection devices AFDD	
Protection main switch	No
Number of poles main switch	4
Main switch rated current	40 A
Protection incoming RCD	No
Protection high integrity	No
Protection split load	No
Protection dual RCD	No
Number of outgoing ways	18
Suitable for data	No
Cooker group	None
Cooker group suitable as power current group	No
With socket outlet	No
With bell transformer	No
Type of over voltage protection device	-
With meter	No
Built-in depth	55 mm

Click-mate NXT distribution boxes equipped with earth leakage circuit breakers 1P+N, 16A, 30mA.