## Distribution boards with earth leakage circuit breakers



## NXT M-6Q-H2 groepenkast

EAN: 8712259534282  Width 220 mm  Height 390 mm  Phases 1-phase wired  Groups 6  Main switch 40 A  Rated current 40 A  Quantity and type of FI/LS switch 6 x RCBO 1P+N, 16A, B-char. 30mA Mounting method Surface mounted (plaster)  Degree of protection (IP) IP20  Width in number of modular spacings 24  Depth 110 mm  Extension possible Yes  Housing material Plastic  Number of phases 1  Lockable Yes
Height390 mmPhases1-phase wiredGroups6Main switch40 ARated current40 AQuantity and type of FI/LS switch6 x RCBO 1P+N, 16A, B-char. 30mA br>Mounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1
Phases 1-phase wired  Groups 6  Main switch 40 A  Rated current 40 A  Quantity and type of FI/LS switch 6 x RCBO 1P+N, 16A, B-char. 30mA Mounting method Surface mounted (plaster)  Degree of protection (IP) IP20  Width in number of modular spacings 24  Depth 110 mm  Extension possible Yes  Housing material Plastic  Number of phases 1
Groups6Main switch40 ARated current40 AQuantity and type of FI/LS switch6 x RCBO 1P+N, 16A, B-char. 30mA Surface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1
Main switch40 ARated current40 AQuantity and type of FI/LS switch6 x RCBO 1P+N, 16A, B-char. 30mA Surface mounted (plaster)Mounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1
Rated current 40 A  Quantity and type of FI/LS switch 6 x RCBO 1P+N, 16A, B-char. 30mA Mounting method Surface mounted (plaster)  Degree of protection (IP) IP20  Width in number of modular spacings 24  Depth 110 mm  Extension possible Yes  Housing material Plastic  Number of phases 1
Quantity and type of FI/LS switch6 x RCBO 1P+N, 16A, B-char. 30mA Surface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1
Mounting method  Degree of protection (IP)  Width in number of modular spacings  Depth  Extension possible  Housing material  Number of phases  Surface mounted (plaster)  IP20  Ves  4  Plastic  Number of phases  Surface mounted (plaster)  IP20  Plastic  Number of phases
Degree of protection (IP)  Width in number of modular spacings  Depth  Extension possible  Housing material  Number of phases  IP20  24  110 mm  Yes  Plastic  Number of phases
Width in number of modular spacings 24  Depth 110 mm  Extension possible Yes  Housing material Plastic  Number of phases 1
Depth 110 mm  Extension possible Yes  Housing material Plastic  Number of phases 1
Extension possible Yes Housing material Plastic Number of phases 1
Housing material Plastic Number of phases 1
Number of phases 1
Lockable
Over voltage protection No
Number of earth leakage switches 30 mA
Number of earth leakage switches 300 mA
With transparent cover No
Protection Miniature- / earth leakage circuit breaker
Total number of groups 6
Number of direct groups
Number of light groups 6
Number of groups behind earth leakage switch
Number of earth leakage circuit breakers 6
Number of arc fault detection devices AFDD
Protection main switch No
Number of poles main switch 2
Main switch rated current 40 A
Protection incoming RCD No
Protection high integrity No
Protection split load No
Protection dual RCD No
Number of outgoing ways 18
Suitable for data No
Cooker group None
Cooker group suitable as power current group No
With socket outlet No
With bell transformer No
Type of over voltage protection device -
With meter No
Built-in depth 55 mm



## **Product data sheet**

Click-mate NXT distribution boxes equipped with earth leakage circuit breakers 1P+N, 16A, 30mA.

