## Distribution boxes with earth leakage switches and circuit breakers



## NXT M-22/22/22-H4 groepenkast

EAN:         8712259534459           Width         220 mm           Height         390 mm           Number of groups (blue)         2           Number of groups (grey)         2           Number of earth fault switches 2P         3-phase wired           Groups         6           Main switch         40 A           Rated current         5 x 32 A           Quantity and type of FI/LS switch         Wounting method           Mounting method         Surface mounted (plaster)           Degree of protection (IP)         IP20           Width in number of modular spacings         24           Extension possible         Yes           Extension possible         Yes           Housing material         Plastic           Number of phases         3           Lockable         Yes           Over voltage protection         No           Number of earth leakage switches 30 mA         3           Number of earth leakage switches 30 mA         3           Number of groups         6           Number of groups behind earth leakage switches 30 mA         3           Number of groups behind earth leakage switches         1           Number of groups behind earth leakage switches	Article no:	AT91553
Height 390 mm Number of groups (blue) 2 Number of groups (ghtblue) 2 Number of groups (grey) 2 Number of earth fault switches 2P 3 Phases 3-phase wired Groups 6 Main switch 40 A Rated current 3x 3x 32 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection Number of earth leakage switches 30 mA With transparent cover No Protection 4 Gilent groups Number of direct groups Number of direct groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of or earth leakage circuit breakers Number of or feroups behind earth leakage switch Number of proups behind earth leakage switch No Number of proups behind earth leakage switch No Number of poles main switch N	EAN:	8712259534459
Number of groups (lightblue)         2           Number of groups (grey)         2           Number of groups (grey)         3           Phases         3-phase wired           Groups         6           Main switch         40 A           Rated current         Surface mounted (plaster)           Quantity and type of FI/LS switch         Wounting method           Mounting method         Surface mounted (plaster)           Degree of protection (IP)         IP20           Width in number of modular spacings         24           Depth         110 mm           Extension possible         Yes           Housing material         Plastic           Number of phases         3           Lockable         Yes           Over voltage protection         No           Number of earth leakage switches 30 mA         3           With transparent cover         No           Protection         Miniature- / earth leakage circuit breaker           Total number of groups         6           Number of direct groups         6           Number of groups behind earth leakage switch         No           Number of poles main switch         No           Number of poles main switch         No<	Width	220 mm
Number of groups (lightblue)         2           Number of earth fault switches 2P         3           Phases         3-phase wired           Groups         6           Main switch         40 A           Rated current         3 x 32 A           Quantity and type of FI/LS switch         Surface mounted (plaster)           Mounting method         Surface mounted (plaster)           Degree of protection (IP)         IP20           Width in number of modular spacings         24           Depth         110 mm           Extension possible         Yes           Housing material         Plastic           Number of phases         3           Lockable         Yes           Over voltage protection         No           Number of earth leakage switches 30 mA         3           Number of earth leakage switches 30 mA         3           With transparent cover         No           Protection         Miniature-/ earth leakage circuit breaker           Number of groups         6           Number of light groups         6           Number of groups behind earth leakage switches         6           Number of earth leakage circuit breakers         1           Number of poles main swit	Height	390 mm
Number of groups (grey)         2           Number of earth fault switches 2P         3           Phases         3-phase wired           Groups         6           Main switch         40 A           Rated current         3 x 32 A           Quantity and type of FI/LS switch         UP20           Mounting method         Surface mounted (plaster)           Degree of protection (IP)         IP20           Width in number of modular spacings         24           Depth         110 mm           Extension possible         Yes           Housing material         Plastic           Number of phases         3           Lockable         Yes           Over voltage protection         No           Number of earth leakage switches 30 mA         3           Number of earth leakage switches 300 mA         3           With transparent cover         No           Protection         Miniature- / earth leakage circuit breaker           Total number of groups         6           Number of direct groups         6           Number of groups behind earth leakage         6           Number of arc fault detection devices AFDD         Yes           Protection main switch         No	Number of groups (blue)	2
Number of earth fault switches 2P         3-phase wired           Groups         6           Main switch         40 A           Rated current         3 x 32 A           Quantity and type of FI/LS switch         Winder mounted (plaster)           Mounting method         Surface mounted (plaster)           Degree of protection (IP)         IP20           Width in number of modular spacings         24           Depth         110 mm           Extension possible         Yes           Housing material         Plastic           Number of phases         3           Lockable         Yes           Over voltage protection         No           Number of earth leakage switches 30 mA         3           With transparent cover         No           Number of earth leakage switches 300 mA         No           With transparent cover         No           Number of groups         6           Number of groups         6           Number of groups         6           Number of light groups         6           Number of earth leakage circuit breakers         1           Number of arc fault detection devices AFDD         1           Protection main switch         No	Number of groups (lightblue)	2
Phases         3-phase wired           Groups         6           Main switch         40 A           Rated current         3 x 32 A           Quantity and type of FI/LS switch         Surface mounted (plaster)           Mounting method         IP20           Vidith in number of protection (IP)         IP20           Width in number of modular spacings         24           Depth         110 mm           Extension possible         Yes           Housing material         Plastic           Number of phases         3           Lockable         Yes           Over voltage protection         No           Number of earth leakage switches 30 mA         3           Number of earth leakage switches 30 mA         3           With transparent cover         No           Protection         Miniature- / earth leakage circuit breaker           Total number of groups         6           Number of light groups         6           Number of light groups         6           Number of sort leakage circuit breakers         No           Number of actfult detection devices AFDD         No           Protection main switch         No           Number of poles main switch         4 <td>Number of groups (grey)</td> <td>2</td>	Number of groups (grey)	2
Groups6Main switch40 ARated current3 x 32 AQuantity and type of FI/LS switchSurface mounted (plaster)Mounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoWith transparent coverMoNumber of direct groups6Number of direct groups6Number of light groups6Number of groups behind earth leakage switch6Number of arct fault detection devices AFDDVertection main switchNoNumber of poles main switchNoNumber of poles main switchNoNumber of poles main switch44Main switch rated current40 AProtection incoming RCDNoProtection fligh integrityNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker group suitable as power current groupNoCooker group suitable as power current groupNo	Number of earth fault switches 2P	3
Main switch Rated current 3 x 32 A  Quantity and type of FI/LS switch  Mounting method Degree of protection (IP) Width in number of modular spacings Depth 110 mm Extension possible Housing material Number of phases Rover voltage protection No Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA  With transparent cover Total number of groups Number of direct groups Number of light groups Roumber of earth leakage circuit breaker Number of earth leakage circuit breaker Number of earth leakage circuit breaker Total number of groups behind earth leakage switch Number of earth leakage circuit breaker Number of of groups behind earth leakage switch Number of far fault detection devices AFDD Protection main switch No Number of poles main switch Adain switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways Suitable for data No Cooker group suitable as power current group No	Phases	3-phase wired
Rated current Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) P20 Width in number of modular spacings 24 Depth 110 mm Extension possible Housing material Number of phases Lockable Ves Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Total number of groups Number of giroups Number of giroups Number of groups behind earth leakage switch Number of earth leakage circuit breaker Number of proups behind earth leakage switch Number of earth leakage circuit breakers Number of or groups behind earth leakage switch Number of light groups Number of proups helind earth leakage switch Number of poles main switch Number of poles main switch Number of poles main switch Namber of poles main switch No Number of poles main switch No No Protection incoming RCD No Protection split load No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group suitable as power current group No	Groups	6
Quantity and type of FI/LS switchSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mA3With transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups6Number of light groups6Number of groups behind earth leakage switch6Number of earth leakage circuit breakers8Number of earth leakage circuit breakers1Number of earth leakage circuit breakers1Number of earth leakage circuit breakers1Number of poles main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker group suitable as power current groupNo	Main switch	40 A
Mounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3With transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups6Number of direct groups6Number of groups behind earth leakage switch6Number of earth leakage circuit breakers6Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection high integrityNoProtection high integrityNoProtection bylit loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker group suitable as power current groupNo	Rated current	3 x 32 A
Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mANoWith transparent coverNoTotal number of groups6Number of direct groups6Number of groups behind earth leakage switch6Number of earth leakage circuit breakers6Number of earth leakage circuit breakers6Number of earth leakage circuit breakersNoNumber of poles main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNone	Quantity and type of FI/LS switch	
Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverProtectionMiniature- / earth leakage circuit breakerTotal number of groups6Number of light groups6Number of groups behind earth leakage switch6Number of earth leakage circuit breakers6Number of earth leakage circuit breakersNoNumber of earth leakage circuit breakersNoNumber of poles main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNone	Mounting method	Surface mounted (plaster)
Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups6Number of direct groups6Number of groups behind earth leakage switch6Number of earth leakage circuit breakers6Number of earth leakage circuit breakersNoNumber of arc fault detection devices AFDDYorProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Degree of protection (IP)	IP20
Extension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups6Number of light groups6Number of groups behind earth leakage switch6Number of arct fault detection devices AFDDVoProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Width in number of modular spacings	24
Housing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups6Number of light groups6Number of groups behind earth leakage switch6Number of arct fault detection devices AFDDVoProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Depth	110 mm
Number of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups6Number of light groups6Number of groups behind earth leakage switch6Number of arct fault detection devices AFDDNoProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Extension possible	Yes
LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups6Number of light groups6Number of groups behind earth leakage switch6Number of groups behind earth leakage switch6Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Housing material	Plastic
Over voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mANoWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups6Number of direct groups6Number of groups behind earth leakage switch6Number of earth leakage circuit breakers6Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection split loadNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Number of phases	3
Number of earth leakage switches 30 mA  Number of earth leakage switches 300 mA  With transparent cover  Protection  Miniature- / earth leakage circuit breaker  Total number of groups  Number of direct groups  Number of light groups  6  Number of groups behind earth leakage switch  Number of earth leakage circuit breakers  Number of acr fault detection devices AFDD  Protection main switch  Number of poles main switch  Number of poles main switch  Adain switch rated current  Protection incoming RCD  No  Protection high integrity  No  Protection split load  Protection dual RCD  Number of outgoing ways  18  Suitable for data  No  Cooker group  None	Lockable	Yes
Number of earth leakage switches 300 mA  With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups 6 Number of direct groups Number of light groups 6 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of arc fault detection devices AFDD  Protection main switch Number of poles main switch Adin switch rated current Protection incoming RCD Protection high integrity No Protection split load No Protection dual RCD No No Number of outgoing ways 18 Suitable for data No Cooker group None	Over voltage protection	No
With transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups6Number of direct groups6Number of groups behind earth leakage switch6Number of earth leakage circuit breakers1Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Number of earth leakage switches 30 mA	3
Protection Miniature- / earth leakage circuit breaker  Total number of groups 6  Number of direct groups  Number of light groups 6  Number of groups behind earth leakage switch  Number of earth leakage circuit breakers  Number of arc fault detection devices AFDD  Protection main switch No  Number of poles main switch 4  Main switch rated current 40 A  Protection incoming RCD No  Protection high integrity No  Protection split load No  Protection dual RCD No  Number of outgoing ways 18  Suitable for data No  Cooker group Suitable as power current group No	Number of earth leakage switches 300 mA	
Total number of groups  Number of direct groups  Number of light groups  6  Number of groups behind earth leakage switch  Number of earth leakage circuit breakers  Number of arc fault detection devices AFDD  Protection main switch  Number of poles main switch  Main switch rated current  A0 A  Protection incoming RCD  Protection high integrity  No  Protection split load  No  Protection dual RCD  Number of outgoing ways  18  Suitable for data  No  Cooker group  Noe	With transparent cover	No
Number of direct groups  Number of light groups 6  Number of groups behind earth leakage switch  Number of earth leakage circuit breakers  Number of arc fault detection devices AFDD  Protection main switch  Number of poles main switch  Main switch rated current  Protection incoming RCD  Protection high integrity  No  Protection split load  Protection dual RCD  Number of outgoing ways  18  Suitable for data  No  Cooker group  No  No  Cooker group suitable as power current group  No  Number of outgoing suitable as power current group  No	Protection	Miniature- / earth leakage circuit breaker
Number of light groups6Number of groups behind earth leakage switch6Number of earth leakage circuit breakersNumber of arc fault detection devices AFDDProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Total number of groups	6
Number of groups behind earth leakage switch  Number of earth leakage circuit breakers  Number of arc fault detection devices AFDD  Protection main switch  Number of poles main switch  Main switch rated current  Protection incoming RCD  No  Protection high integrity  No  Protection split load  No  Protection dual RCD  Number of outgoing ways  18  Suitable for data  No  Cooker group  No  No  No  No  No  No  No  No  No  N	Number of direct groups	
Number of earth leakage circuit breakers  Number of arc fault detection devices AFDD  Protection main switch  Number of poles main switch  Number of poles main switch  Main switch rated current  Protection incoming RCD  No  Protection high integrity  No  Protection split load  Protection dual RCD  No  No  Number of outgoing ways  18  Suitable for data  No  Cooker group  None  Cooker group suitable as power current group  No	Number of light groups	6
Number of arc fault detection devices AFDD  Protection main switch No Number of poles main switch Ad Main switch rated current Ad Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No		6
Protection main switch Number of poles main switch Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Number of earth leakage circuit breakers	
Number of poles main switch  Main switch rated current  40 A  Protection incoming RCD  No  Protection high integrity  No  Protection split load  No  Protection dual RCD  No  Number of outgoing ways  18  Suitable for data  Cooker group  None  Cooker group suitable as power current group  No	Number of arc fault detection devices AFDD	
Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Protection main switch	No
Protection incoming RCD  Protection high integrity  No  Protection split load  No  Protection dual RCD  No  Number of outgoing ways  Suitable for data  Cooker group  No  None  None	Number of poles main switch	4
Protection high integrity  Protection split load  Protection dual RCD  No  Number of outgoing ways  Suitable for data  Cooker group  None  Cooker group suitable as power current group  No	Main switch rated current	40 A
Protection split load Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Protection incoming RCD	No
Protection dual RCD Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Protection high integrity	No
Number of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Protection split load	No
Suitable for data  Cooker group  None  Cooker group suitable as power current group  No	Protection dual RCD	No
Cooker group None Cooker group suitable as power current group No	Number of outgoing ways	18
Cooker group suitable as power current group No	Suitable for data	No
	Cooker group	None
With socket outlet No	Cooker group suitable as power current group	No
	With socket outlet	No



With bell transformer	No
Type of over voltage protection device	-
With meter	No
Built-in depth	55 mm

The new generation of Click-mate NXT distribution boxes is available in various editions: The compact S distribution cabinet with 12 modules, the familiar M distribution cabinet with space for 2 x 12 modules and the innovative L distribution cabinet with 2 x 18 modules; the solution for the energy transition and extensive 3-phase installations. The distribution boxes are also completely modular and can easily be installed next to or underneath each other. The distribution boxes in the extensive range are equipped with earth leakage circuit breakers (2P, 40A, 30mA) and circuit breakers (1P+N, 16A, B-characteristic) and are optionally available with a stove group and/or bell transformer.

