Distribution boxes with earth leakage switches and circuit breakers



NXT M-23/23/23-H4 groepenkast

EAN: 8712259534602 Width 220 mm Height 390 mm Number of groups (blue) 3 Number of groups (grey) 3 Number of earth fault switches 2P 3 Phases 3-phase wired Groups 9 Main switch 40 A Rated current \$ 3x 32 A Quantity and type of FIVLS switch Wounting method Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Etension possible Yes Etension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 3 Vith transparent cover No Protection Miniature-/ earth leakage circuit breaker Number of groups behind earth leakage switches 9 Number of light groups 9 Number of	Article no:	AT91568
Height 390 mm Number of groups (blue) 3 Number of groups (ghtblue) 3 Number of groups (grey) 3 Number of earth fault switches 2P 3 Phases 3-phase wired Groups 9 Main switch 40 A Rated current 3x 3x 32 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection Number of earth leakage switches 30 mA With transparent cover No Protection 4 Gilent groups Number of direct groups Number of direct groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of or earth leakage circuit breakers Number of or feroups 9 Number of groups behind earth leakage switch Number of proups behind earth leakage switch Number of earth leakage circuit breakers Number of light groups Number of poles main switch No Number of poles main switch No Number of poles main switch No Number of poles main switch A Main switch rated current A Main switch rated current No Protection incoming RCD No Protection high integrity No Protection split load No Protection outgoing ways 18 Suitable for data No Cooker group suitable as power current group Cooker group suitable as power current group	EAN:	8712259534602
Number of groups (blue)3Number of groups (rightblue)3Number of groups (grey)3Number of earth fault switches 2P3Phases3-phase wiredGroups9Main switch40 ARated currentSurface mounted (plaster)Quantity and type of FI/LS switchWounting methodMounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possiblePlasticHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 30 mA3Number of earth leakage switches 30 mANoWith transparent coverNoProtectionMiniature-/ earth leakage circuit breakerTotal number of groups9Number of direct groups9Number of groups behind earth leakage9Number of earth leakage circuit breakersNoNumber of earth leakage circuit breakersNoNumber of poles main switchNoNumber of proups behind earth leakage9Number of proups behind earth leakage9Number of poles main switchNoNumber of poles main switchNoNumber of poles main switchNoMain switch rated currentNoProtection high integrityNo <t< td=""><td>Width</td><td>220 mm</td></t<>	Width	220 mm
Number of groups (lightblue) 3 Number of earth fault switches 2P 3 Phases 3-phase wired Groups 9 Main switch 40 A Rated current 3 x 32 A Quantity and type of FI/LS switch Fire mounted (plaster) Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 3 Number of earth leakage switches 30 mA 3 With transparent cover No Nortection Miniature-/ earth leakage circuit breaker Number of groups 9 Number of light groups 9 Number of of groups behind earth leakage switches 9 Number of earth leakage circuit breakers 1 Number of poles main swit	Height	390 mm
Number of groups (grey) 3 Number of earth fault switches 2P 3 Phases 3-phase wired Groups 9 Main switch 40 A Rated current 3 x 32 A Quantity and type of FI/LS switch UP20 Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 3 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 9 Number of direct groups 9 Number of groups behind earth leakage 9 Number of arc faut detection devices AFDD Yes Number of poles main switch No Nu	Number of groups (blue)	3
Number of earth fault switches 2P3Phases3-phase wiredGroups9Main switch40 ARated current3 x 32 AQuantity and type of FI/LS switchWiffice mounted (plaster)Mounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mAWith transparent coverWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of direct groups9Number of light groups9Number of arc fault detection devices AFDDYesProtection main switchNoNumber of poles main switchNoAlain switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection dula RCDNoNumber of outgoing ways18Suitable for dataNoCooker group suitable as power current groupNoCooker group suitable as power current groupNo	Number of groups (lightblue)	3
Phases 3-phase wired Groups 9 Main switch 40 A Rated current 3 x 32 A Quantity and type of FI/LS switch Surface mounted (plaster) Mounting method IP20 Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 3 Number of earth leakage switches 30 mA 3 With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 9 Number of light groups 9 Number of light groups 9 Number of soroups behind earth leakage switch 9 Number of act full detection devices AFDD No Protection main switch No Number of poles main switch 4	Number of groups (grey)	3
Groups 9 Main switch 40 A Rated current 3 x 32 A Quantity and type of FI/LS switch Surface mounted (plaster) Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 3 Number of earth leakage switches 300 mA 3 With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 9 Number of direct groups 9 Number of light groups 9 Number of groups behind earth leakage switch 9 Number of earth leakage circuit breakers No Number of poles main switch No Number of poles main switch No Muin switch rated	Number of earth fault switches 2P	3
Main switch40 ARated current3 x 32 AQuantity and type of FI/LS switchSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3With transparent coverNoTotal number of groups9Number of direct groups9Number of light groups9Number of earth leakage circuit breaker9Number of groups behind earth leakage9switchNoNumber of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Phases	3-phase wired
Rated current Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) P20 Width in number of modular spacings 24 Depth 110 mm Extension possible Housing material Number of phases Lockable Ves Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Total number of groups Number of gildt groups Number of groups behind earth leakage switch Number of earth leakage circuit breaker Number of proups Popus behind earth leakage switch Number of earth leakage circuit breaker Number of or fac fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection high integrity No Protection split load No Protection split load No Nome Cooker group suitable as power current group Cooker group suitable as power current group None Cooker group suitable as power current group No Ne Cooker group suitable as power current group No Ne Protection rain suitable as power current group No No Protection dual RCD No No None Cooker group suitable as power current group No No Protection dual RCD None Cooker group suitable as power current group No No Protection dual RCD None Cooker group suitable as power current group No No Protection figure protection dual RCD None Cooker group suitable as power current group No No Protection figure protection dual RCD None Cooker group suitable as power current group No No Protection figure protection dual RCD No No No Protection figure protection dual RCD No No No Cooker group suitable as power current group No No Protection figure protection dual RCD No No No Protection figure protection dual RCD No No No Protection figure protection dual RCD No No No Protection figure protection	Groups	9
Quantity and type of FI/LS switchSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mA3With transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of light groups9Number of groups behind earth leakage switch9Number of earth leakage circuit breakers9Number of earth leakage circuit breakersNoNumber of poles main switchNoNumber of poles main switchNoMain switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker group suitable as power current groupNo	Main switch	40 A
Mounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3With transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of direct groups9Number of groups behind earth leakage9Number of earth leakage circuit breakers9Number of earth leakage circuit breakersNoNumber of poles main switchNoNumber of poles main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection bylit loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Rated current	3 x 32 A
Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mANoWith transparent coverNoTotal number of groups9Number of direct groups9Number of groups behind earth leakage switch9Number of groups behind earth leakage switch9Number of earth leakage circuit breakers9Number of earth leakage circuit breakersNoNumber of poles main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Quantity and type of FI/LS switch	
Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of light groups9Number of groups behind earth leakage switch9Number of arc fault detection devices AFDD9Protection main switchNoNumber of poles main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker group suitable as power current groupNo	Mounting method	Surface mounted (plaster)
Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of direct groups9Number of groups behind earth leakage switch9Number of earth leakage circuit breakers9Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Degree of protection (IP)	IP20
Extension possibleYesHousing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of light groups9Number of groups behind earth leakage switch9Number of arct fault detection devices AFDDYesProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Width in number of modular spacings	24
Housing materialPlasticNumber of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of light groups9Number of groups behind earth leakage switch9Number of arct fault detection devices AFDDYesProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Depth	110 mm
Number of phases3LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of light groups9Number of groups behind earth leakage switch9Number of arct fault detection devices AFDDYesProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Extension possible	Yes
LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mAWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of light groups9Number of groups behind earth leakage switch9Number of groups behind earth leakage switch9Number of arc fault detection devices AFDDNoProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Housing material	Plastic
Over voltage protectionNoNumber of earth leakage switches 30 mA3Number of earth leakage switches 300 mANoWith transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of direct groups9Number of groups behind earth leakage switch9Number of groups behind earth leakage switch9Number of earth leakage circuit breakersNumber of arc fault detection devices AFDDProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Number of phases	3
Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of light groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of acr fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways 18 Suitable for data Cooker group No No No No No No No No No N	Lockable	Yes
Number of earth leakage switches 300 mA With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups 9 Number of direct groups Number of light groups 9 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Adin switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways 18 Suitable for data Cooker group suitable as power current group No	Over voltage protection	No
With transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups9Number of direct groups9Number of groups behind earth leakage switch9Number of earth leakage circuit breakers1Number of arc fault detection devices AFDD1Protection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Number of earth leakage switches 30 mA	3
Protection Miniature- / earth leakage circuit breaker Total number of groups 9 Number of direct groups Number of light groups 9 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 4 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group No	Number of earth leakage switches 300 mA	
Total number of groups Number of direct groups Number of light groups 9 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Adain switch rated current Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD Number of outgoing ways 18 Suitable for data No Cooker group Suitable as power current group No	With transparent cover	No
Number of direct groups Number of light groups Possible of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways 18 Suitable for data No Cooker group No No No No No No No No No N	Protection	Miniature- / earth leakage circuit breaker
Number of light groups9Number of groups behind earth leakage switch9Number of earth leakage circuit breakersNumber of arc fault detection devices AFDDProtection main switchNoNumber of poles main switch4Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Total number of groups	9
Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD Number of outgoing ways 18 Suitable for data No Cooker group No No No No No No No No No N	Number of direct groups	
Switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Number of light groups	9
Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Ad Main switch rated current Ad Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	3 .	9
Protection main switch Number of poles main switch Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Number of earth leakage circuit breakers	
Number of poles main switch Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group None Cooker group suitable as power current group No	Number of arc fault detection devices AFDD	
Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Protection main switch	No
Protection incoming RCD Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways Suitable for data Cooker group No None None	Number of poles main switch	4
Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group None Cooker group suitable as power current group No	Main switch rated current	40 A
Protection split load Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Protection incoming RCD	No
Protection dual RCD Number of outgoing ways 18 Suitable for data No Cooker group None Cooker group suitable as power current group No	Protection high integrity	No
Number of outgoing ways18Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Protection split load	No
Suitable for data Cooker group None Cooker group suitable as power current group No	Protection dual RCD	No
Cooker group None Cooker group suitable as power current group No	Number of outgoing ways	18
Cooker group suitable as power current group No	Suitable for data	No
	Cooker group	None
With socket outlet No	Cooker group suitable as power current group	No
	With socket outlet	No



With bell transformer	No
Type of over voltage protection device	-
With meter	No
Built-in depth	55 mm

The new generation of Click-mate NXT distribution boxes is available in various editions: The compact S distribution cabinet with 12 modules, the familiar M distribution cabinet with space for 2 x 12 modules and the innovative L distribution cabinet with 2 x 18 modules; the solution for the energy transition and extensive 3-phase installations. The distribution boxes are also completely modular and can easily be installed next to or underneath each other. The distribution boxes in the extensive range are equipped with earth leakage circuit breakers (2P, 40A, 30mA) and circuit breakers (1P+N, 16A, B-characteristic) and are optionally available with a stove group and/or bell transformer.

