

Distribution boxes with earth leakage switches and circuit breakers



NXT M-23/23F/23-H4 groepenkast

| | |
|----------------------------------------------|--------------------------------------------|
| Article no: | AT91569 |
| EAN: | 8712259534619 |
| Width | 220 mm |
| Height | 390 mm |
| Number of groups (blue) | 3 |
| Number of groups (lightblue) | 3 |
| Number of groups (grey) | 4 |
| Number of earth fault switches 2P | 3 |
| Phases | 3-phase wired |
| Groups | 10 |
| Cooking group | 1-phase (F) |
| Main switch | 40 A |
| Rated current | 3 x 32 A |
| Quantity and type of FI/LS switch | |
| Mounting method | Surface mounted (plaster) |
| Degree of protection (IP) | IP20 |
| Width in number of modular spacings | 24 |
| Depth | 110 mm |
| Extension possible | Yes |
| Housing material | Plastic |
| Number of phases | 3 |
| Lockable | Yes |
| Over voltage protection | No |
| Number of earth leakage switches 30 mA | 3 |
| Number of earth leakage switches 300 mA | |
| With transparent cover | No |
| Protection | Miniature- / earth leakage circuit breaker |
| Total number of groups | 10 |
| Number of direct groups | |
| Number of light groups | 9 |
| Number of groups behind earth leakage switch | 10 |
| Number of earth leakage circuit breakers | |
| Number of arc fault detection devices AFDD | |
| Protection main switch | No |
| Number of poles main switch | 4 |
| Main switch rated current | 40 A |
| Protection incoming RCD | No |
| Protection high integrity | No |
| Protection split load | No |
| Protection dual RCD | No |
| Number of outgoing ways | 18 |
| Suitable for data | No |
| Cooker group | Single phase |
| Cooker group suitable as power current group | No |

| | |
|----------------------------------------|-------|
| With socket outlet | No |
| With bell transformer | No |
| Type of over voltage protection device | - |
| With meter | No |
| Built-in depth | 55 mm |

The new generation of Click-mate NXT distribution boxes is available in various editions: The compact S distribution cabinet with 12 modules, the familiar M distribution cabinet with space for 2 x 12 modules and the innovative L distribution cabinet with 2 x 18 modules; the solution for the energy transition and extensive 3-phase installations. The distribution boxes are also completely modular and can easily be installed next to or underneath each other. The distribution boxes in the extensive range are equipped with earth leakage circuit breakers (2P, 40A, 30mA) and circuit breakers (1P+N, 16A, B-characteristic) and are optionally available with a stove group and/or bell transformer.