Extension boxes



NXT M3-44/44/00 groepenkast

EAN: 8712259534794 Width 220 mm Height 390 mm Number of groups (blue) 4 Number of groups (grey) 4 Number of groups (grey) 4 Number of earth fault switches 4P 2 Phases 3-phase wired Groups 8 Main switch None Rated current 3 x 32 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 1110 mm Extension possible Yes Housing material Plastic Number of parth leakage switches 30 mA Number of earth leakage switches 30 mA Vith transparent cover No Number of earth leakage switches 300 mA With transparent cover Total number of groups Number of light groups Number of direct groups Number of groups 8 Number of light groups Number of groups behind earth leakage switch Number of arth leakage circuit breakers Number of arcfault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection split load No Protection split load Protection dual RCD No None Cooker group Suitable as power current group Cooker group suitable as power current group Cooker group suitable as power current group Ves	Article no:	AT91587
Height 390 mm Number of groups (blue) 4 Number of groups (grey) 4 Number of groups (grey) 4 Number of earth fault switches 4P 2 Phases 3-phase wired Groups 8 Main switch None Rated current 3 x 32 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of light groups 8 Number of groups 8 Number of groups 8 Number of are fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection light fired Protection ligh integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	EAN:	8712259534794
Number of groups (blue) Number of groups (grey) A Number of arth fault switches 4P Phases 3-phase wired Groups 8 Main switch None Rated current 3 x 32 A Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings Depth 110 mm Extension possible Yes Housing material Number of phases 1 Cover voltage protection None Number of earth leakage switches 30 mA With transparent cover No Protection Total number of groups behind earth leakage switch Number of mouse of groups Number of groups behind earth leakage switch Number of olight groups No No No Number of poles main switch No Number of poles main switch No Number of poles main switch Main switch rated current Protection high integrity No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group	Width	220 mm
Number of groups (grey) 4 Number of earth fault switches 4P 2 Phases 3-phase wired Groups 8 Main switch None Rated current 3 x 32 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection Number of earth leakage switches 30 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of direct groups Number of earth leakage circuit breakers Number of aerth leakage circuit breaker Number of groups behind earth leakage switch Number of groups behind earth leakage switch Number of groups behind earth leakage switch Number of plast groups Number of groups behind earth leakage switch Number of plast groups Number of groups behind earth leakage switch Number of poles main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Height	390 mm
Number of earth fault switches 4P Phases Groups 8 Main switch None Rated current 3 x 32 A Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings Pepth Housing material Number of phases Lockable Ves Over voltage protection No Number of earth leakage switches 30 mA With transparent cover Protection Protection Sumber of groups Number of earth leakage circuit breaker Number of plight groups Number of groups 8 Number of earth leakage circuit breakers Number of or groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch Main switch rated current Protection fligh integrity No Protection flugh integrity No Protection dual RCD No Number of outgoing ways Suitable for data Cooker group None	Number of groups (blue)	4
Phases 3-phase wired Groups 8 Main switch None Rated current 3 x 32 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 1110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA Vith transparent cover No Protection direct groups Number of direct groups Number of direct groups Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection ricoming RCD No Protection dual RCD No Number of outgoing ways Suitable for data No Cooker group None	Number of groups (grey)	4
Groups 8 Main switch None Rated current 3 x 32 A Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA Vith transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of light groups 8 Number of groups behind earth leakage switch Number of earth leakage circuit breaker Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Number of earth fault switches 4P	2
Main switch Rated current 3 x 32 A Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Degree of protection (IP) Width in number of modular spacings Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Over voltage protection Number of earth leakage switches 30 mA Vith transparent cover No Protection Total number of groups Number of light groups Number of earth leakage switches Number of earth leakage switches Number of of groups behind earth leakage switch Number of proups Number of direct groups Number of earth leakage circuit breaker Number of poles main switch Number of earth leakage circuit breakers Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group None	Phases	3-phase wired
Rated current Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) Width in number of modular spacings Depth 110 mm Extension possible Housing material Number of phases 3 Lockable Over voltage protection No Number of earth leakage switches 30 mA With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Number of light groups Number of groups 8 Number of groups 8 Number of or groups 8 Number of or groups 8 Number of proups 9 Number of poles main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection split load No Protection split load No Protection split load No Protection outgoing ways 18 Suitable for data Cooker group None	Groups	8
Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of acr fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group None	Main switch	None
Mounting method Degree of protection (IP) Uidth in number of modular spacings Depth 110 mm Extension possible Housing material Number of phases Lockable Ves Over voltage protection Number of earth leakage switches 30 mA With transparent cover Protection Total number of groups Number of groups Number of groups Number of earth leakage circuit breaker Total number of groups Number of earth leakage circuit breakers Number of ore arth leakage circuit breaker Total number of groups Number of light groups Number of proups behind earth leakage switch Number of ore carth leakage circuit breakers Number of ore farth leakage circuit breakers Number of proups behind earth leakage switch Number of poles main switch Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data Cooker group None	Rated current	3 x 32 A
Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of groups 8 Number of groups 8 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of poles main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Quantity and type of FI/LS switch	
Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of groups 8 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of poles main switch No No No Protection main switch No No Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Mounting method	Surface mounted (plaster)
Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA Vith transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of groups 8 Number of groups behind earth leakage switch Number of groups behind earth leakage switch Number of protection Sumpariate over No Number of proups Number of light groups Number of light groups Number of proups Number of groups Number of groups Number of groups Number of groups Number of protection devices AFDD Protection main switch No Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Degree of protection (IP)	IP20
Extension possible Yes Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of groups 8 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Width in number of modular spacings	24
Housing material Plastic Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of light groups 8 Number of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Depth	110 mm
Number of phases 3 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of light groups 8 Number of groups behind earth leakage switch Number of arth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Extension possible	Yes
Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of light groups 8 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Housing material	Plastic
Over voltage protection No Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of light groups 8 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Number of phases	3
Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of light groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection dual RCD Number of outgoing ways 18 Suitable for data No None	Lockable	Yes
Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of light groups 8 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Over voltage protection	No
With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of light groups Rumber of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways No Suitable for data No Cooker group No Miniature- / earth leakage circuit breaker 8 Number - / earth leakage circuit breaker No	Number of earth leakage switches 30 mA	2
Protection Miniature- / earth leakage circuit breaker Total number of groups 8 Number of direct groups Number of light groups 8 Number of groups behind earth leakage 8 switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Number of earth leakage switches 300 mA	
Total number of groups Number of direct groups Number of light groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load No Protection dual RCD Number of outgoing ways No Suitable for data No Cooker group No No Number of direct groups No	With transparent cover	No
Number of direct groups Number of light groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways 18 Suitable for data No Cooker group Number of light groups 8 Number of groups behind earth leakage services No No No No No No No No No N	Protection	Miniature- / earth leakage circuit breaker
Number of light groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways 18 Suitable for data No Cooker group Number of groups sehind earth leakage 8 8 Number of arc fault detection devices AFDD No No No No No No No No No	Total number of groups	8
Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways 18 Suitable for data No Cooker group None	Number of direct groups	
Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways Suitable for data Cooker group Number of None	Number of light groups	8
Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways Suitable for data Cooker group No No No No No No No No No N		8
Protection main switch Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group No	Number of earth leakage circuit breakers	
Number of poles main switch Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Number of arc fault detection devices AFDD	
Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Protection main switch	No
Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group No No No None	Number of poles main switch	
Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group No No No None	Main switch rated current	
Protection split load No Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Protection incoming RCD	No
Protection dual RCD No Number of outgoing ways 18 Suitable for data No Cooker group None	Protection high integrity	No
Number of outgoing ways Suitable for data Cooker group None	Protection split load	No
Suitable for data No Cooker group None	Protection dual RCD	No
Cooker group None	Number of outgoing ways	18
	Suitable for data	No
Cooker group suitable as power current group Yes	Cooker group	None
	Cooker group suitable as power current group	Yes
With socket outlet No	With socket outlet	No
With bell transformer No	With bell transformer	No



Type of over voltage protection device	-
With meter	No
Built-in depth	55 mm

Click-mate NXT distribution boxes without main switch. To expand existing installations.

