Click-mate NXT | Pluggable distribution boards



NXT MWI-22/22/00-H2 groepenkast

EAN: Wridth 220 mm Height 390 mm Number of groups (blue) 2 Number of groups (grey) 2 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Main switch 40 A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Wridth in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Voer voltage protection Phases 1 Lockable Yes Nomber of earth leakage switches 300 mA Writh transparent cover No Protection Groups 4 Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection high integrity No Protection high integrity No Protection high integrity No Protection incoming RCD No Number of outgoing ways 4 Suitable for data No Cooker group suitable as power current group With socket outlet (Vith Schele) United Schele outlet on the schele outlet outlet outlet on the schele outlet outl	Article no:	AT91594
Height 390 mm Number of groups (blue) 2 Number of groups (grey) 2 Number of arch fault switches 2P 2 Phases 1-phase wired Groups 4 Main switch 40 A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups Number of light groups 4 Number of groups behind earth leakage witch Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Nome Cooker group suitable as power current group None	EAN:	8712259535401
Number of groups (blue) 2 Number of groups (grey) 2 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 4 Main switch 40 A Rated current 40 A Rated current 50 Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection 4 Number of groups A Number of groups behind earth leakage switch Number of groups behind earth leakage switch Number of earth leakage circuit breaker Total number of groups 4 Number of earth leakage circuit breaker Total number of groups 4 Number of of light groups 4 Number of of light groups 4 Number of oarth leakage circuit breaker Number of poles main switch No Number of poles main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection split load No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group Suitable as power current group	Width	220 mm
Number of groups (grey) Number of earth fault switches 2P Phases 1-phase wired Groups 4 Main switch 40 A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Number of phases 1 Lockable Over voltage protection No Number of earth leakage switches 30 mA With transparent cover Notal number of groups Number of direct groups Number of groups behind earth leakage switch Number of groups behind earth leakage switches switch Number of arc fault detection devices AFDD Protection main switch No No Protection nicoming RCD No No Protection split load Protection split load Protection nicoming RCD No No No Protection dal RCD No No No Cooker group suitable as power current group No No Cooker group suitable as power current group No No No No Postection under No No No No No No No No No N	Height	390 mm
Number of earth fault switches 2P Phases 1-phase wired Groups 4 Main switch Ad A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Pegree of protection (IP) Peth Beth Beth Beth Beth Beth Beth Beth B	Number of groups (blue)	2
Phases 1-phase wired Groups 4 Main switch 40 A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups Number of light groups 4 Number of groups 4 Number of groups 4 Number of groups 4 Number of are fault detection devices AFDD Protection min switch No Number of poles main switch 2 Main switch rated current 40 A Protection light grity No Protection incoming RCD No Protection dual RCD No None Cooker group suitable as power current group Cooker group suitable as power current group Cooker group suitable as power current group None	Number of groups (grey)	2
Groups 4 Main switch 40 A Rated current 40 A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of direct groups Number of direct groups 4 Number of groups behind earth leakage switch Number of aerth leakage circuit breakers Number of aerth leakage circuit breakers Number of groups behind earth leakage switch Number of poles main switch No Number of poles main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dala RCD No Number of outgoing ways 4 Suitable for data No Cooker group Suitable as power current group Cooker group suitable as power current group	Number of earth fault switches 2P	2
Main switch 40 A Rated current 40 A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of acr fault detection devices AFDD Protection main switch No Number of poles main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection ligh integrity No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group suitable as power current group Cooker group suitable as power current group Cooker group suitable as power current group No	Phases	1-phase wired
Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups 4 Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Nome Cooker group suitable as power current group None	Groups	4
Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups Number of light groups Number of groups behind earth leakage 4 Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of proups 4 Number of groups behind earth leakage 4 Switch Number of paces main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group Suitable as power current group None	Main switch	40 A
Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of groups behind earth leakage switch Number of poles main switch No Number of poles main switch No Number of poles main switch No Protection incoming RCD No Protection dual RCD No Nome Cooker group suitable as power current group None Cooker group suitable as power current group No	Rated current	40 A
Mounting method Degree of protection (IP) Width in number of modular spacings Depth 110 mm Extension possible Housing material Number of phases 1 Lockable Over voltage protection Number of earth leakage switches 30 mA Vith transparent cover Notal number of groups Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Vere Number of phases Vere Ves Over voltage protection No No No No Protection Miniature- / earth leakage circuit breaker Total number of groups A Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of poles main switch No No No Protection main switch No Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No No None Cooker group suitable as power current group No	Connector type	Wieland GST18
Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups 4 Number of proups behind earth leakage switch Number of poes main switch No Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No No Number of outgoing ways 4 Suitable for data No Cooker group Suitable as power current group No	Quantity and type of FI/LS switch	
Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of poles main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group suitable as power current group No	Mounting method	Surface mounted (plaster)
Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of oarc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group suitable as power current group No	Degree of protection (IP)	IP20
Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group Suitable as power current group No	Width in number of modular spacings	24
Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of groups behind earth leakage switch Number of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group suitable as power current group No	Depth	110 mm
Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group Suitable as power current group No	Extension possible	Yes
Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group Suitable as power current group No	Housing material	Plastic
Over voltage protection No Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of acr fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group suitable as power current group No	Number of phases	1
Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Number of light groups Number of light groups A umber of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Protection incoming RCD Protection high integrity No Protection dual RCD Number of outgoing ways 4 Suitable for data No Cooker group No No No No No No No No No N	Lockable	Yes
Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group Suitable as power current group No	Over voltage protection	No
With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups A Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group No	Number of earth leakage switches 30 mA	2
Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group Suitable as power current group No	Number of earth leakage switches 300 mA	
Total number of groups Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Ain switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways Suitable for data Cooker group No No No No No No No No No N	With transparent cover	No
Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch A No Number of poles main switch Protection incoming RCD Protection high integrity No Protection split load No Protection dual RCD Number of outgoing ways A Suitable for data Cooker group No No No No No No No No No N	Protection	Miniature- / earth leakage circuit breaker
Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group Suitable as power current group No	Total number of groups	4
Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Ad A Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways Suitable for data Cooker group Cooker group suitable as power current group No	Number of direct groups	
Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Protection incoming RCD No Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways Au Suitable for data No Cooker group No No No No No No No No No N	Number of light groups	4
Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Nain switch rated current Au A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways Au Suitable for data No Cooker group Cooker group suitable as power current group No	- · · · · - · · · · · · · · · · · · · ·	4
Protection main switch Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group South and switch No No None Cooker group suitable as power current group No	Number of earth leakage circuit breakers	
Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group None Cooker group suitable as power current group No	Number of arc fault detection devices AFDD	
Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group None Cooker group suitable as power current group No	Protection main switch	No
Protection incoming RCD Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data Cooker group None Cooker group suitable as power current group No	Number of poles main switch	2
Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group None Cooker group suitable as power current group No	Main switch rated current	40 A
Protection split load No Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group None Cooker group suitable as power current group No	Protection incoming RCD	No
Protection dual RCD No Number of outgoing ways 4 Suitable for data No Cooker group None Cooker group suitable as power current group No	Protection high integrity	No
Number of outgoing ways4Suitable for dataNoCooker groupNoneCooker group suitable as power current groupNo	Protection split load	No
Suitable for data Cooker group Cooker group suitable as power current group No	Protection dual RCD	No
Cooker group Suitable as power current group No	Number of outgoing ways	4
Cooker group suitable as power current group No	Suitable for data	No
	Cooker group	None
With socket outlet No	Cooker group suitable as power current group	No
	With socket outlet	No



With bell transformer	No	
Type of over voltage protection device	-	
With meter	No	
Built-in depth		

The group boxes for "pluggable installation" are equipped with an output bridge with (optional) Wieland GST18 or WAGO Winsta Midi connectors. The fully pre-wired pluggable output bridge can be fitted with a maximum of 9 to 13 connectors for 1-phase end groups. Connections for electric cooking, mechanical ventilation or power groups have also been taken into account: space has been reserved in the output bridge for a maximum of 2 to 4 pieces of 5-pole connectors. All connectors are pre-wired with 2.5 mm² and fitted with locking as standard. Almost all "traditional" group boxes can be equipped with a fully pre-wired pluggable output bridge with Wieland GST18 or WAGO Winsta Midi connectors. Just like the standard group boxes, the pluggable group boxes are also fully assembled by Attema within a few days according to your wishes. If you are looking for a different configuration, you can put together your own pluggable group box in no time at all.

