Click-mate NXT | Pluggable distribution boards



NXT MWI-22/22F/00-H2 groepenkast

EAN: 8712259535418 Width 220 mm Height 390 mm Number of groups (blue) 2 Number of groups (grey) 3 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 5 Cooking group 1-phase (F) Main switch 40 A Rated current 40 A Rated current 40 A Rountity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 300 mA With transparent cover No Number of groups 5 Number of groups 5 Number of light groups 4 Number of light groups 5 Number of earth leakage circuit breaker Number of aerth leakage circuit breakers Number of poles main switch No Number of poles main switch 12 Main switch rated current 40 A Protection incoming RCD No Protection split load No Protection plit load No Protection plit load No Protection dual RCD No No Nomer of outgoing ways 5 Suitable for data No Cooker group Single phase Cooker group suitable as power current group Cooker group suitable as power current group	Article no:	AT91595
Height 390 mm Number of groups (blue) 2 Number of groups (grey) 3 Number of groups (grey) 3 Number of earth fault switches 2P 2 Phases 1-phase wired Groups 5 Cooking group 1-phase (F) Main switch 40 A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Pepth Using material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups Number of groups 5 Number of direct groups Number of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch No Number of pose main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	EAN:	8712259535418
Number of groups (blue) Number of groups (grey) Number of earth fault switches 2P Phases 1-phase wired Groups 5 Cooking group 1-phase (F) Main switch At 0 A Rated current 40 A Rated current 40 A Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth Extension possible Yes Housing material Number of phases 1 Lockable Yes Voer voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Number of groups behind earth leakage switch Number of groups behind earth leakage switch Number of acr fault detection devices AFDD Protection main switch No Number of pose main switch No Number of pose main switch No Protection incoming RCD No Protection dul RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Width	220 mm
Number of groups (grey) Number of earth fault switches 2P Phases 1-phase wired Groups 5 Cooking group 1-phase (F) Main switch 40 A Rated current 40 A Connector type Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings Phasic Number of phases 1 Lockable Ves Over voltage protection No Number of earth leakage switches 30 mA With transparent cover Total number of groups No No No Protection main switch No Number of poles main switch No Number of poles main switch No Protection incoming RCD No Protection dual RCD No Number of outgoing ways Siutable for data No Cooker group Single phase	Height	390 mm
Number of earth fault switches 2P Phases 1-phase wired Groups 5 Cooking group 1-phase (F) Main switch 40 A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings Depth 110 mm Extension possible Yes Housing material Number of phases 1 Lockable Ves Over voltage protection Number of earth leakage switches 30 mA With transparent cover No Protection Total number of groups Number of groups Number of groups behind earth leakage switch Number of poles main switch No No Protection incoming RCD No Protection spil load No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Number of groups (blue)	2
Phases 1-phase wired Groups 5 Cooking group 1-phase (F) Main switch 40 A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of direct groups Number of earth leakage circuit breakers Number of earth leakage circuit breaker Total number of groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of groups behind earth leakage switch Number of plass in switch 2 Main switch rated current 40 A Protection nain switch No No Protection high integrity No Protection dual RCD No No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Number of groups (grey)	3
Groups 5 Cooking group 1-phase (F) Main switch 40 A Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA Viith transparent cover No Protection Groups 5 Number of direct groups Number of groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breaker Switch Number of earth leakage circuit breakers Number of of groups 5 Number of filight groups 4 Number of of groups behind earth leakage switch Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Number of earth fault switches 2P	2
Cooking group Main switch A0 A Rated current 40 A Rated current 40 A Connector type Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings Depth Extension possible Housing material Number of phases 1 Lockable Over voltage protection No Number of earth leakage switches 30 mA With transparent cover Protection Total number of groups Number of direct groups Number of groups behind earth leakage switch Number of earth leakage circuit breaker Number of groups behind earth leakage switch Number of or arc fault detection devices AFDD Protection main switch No Number of poles main switch Ain switch rated current Protection split load Protection dal RCD No Number of outgoing ways Suitable for data No Cooker group Surface mounted (plaster) Wieland GST18 40 A Protection Miniature-/ 40 A Protection incoming RCD No No No No Protection split load No Protection dal RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Phases	1-phase wired
Main switch Rated current 40 A Rated current 40 A Connector type Quantity and type of FI/LS switch Mounting method Degree of protection (IP) Width in number of modular spacings Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Over voltage protection Number of earth leakage switches 30 mA With transparent cover Protection Total number of groups Number of direct groups Number of groups behind earth leakage switch Number of earth leakage circuit breaker Number of proups behind earth leakage switch Number of proups 5 Number of of groups behind earth leakage switch Number of poles main switch No Number of poles main switch No Number of poles main switch No Protection nicoming RCD Protection high integrity No Protection dual RCD No Number of outgoing ways Suitable for data No Cooker group Surface mounted (plaster) Surface mounted	Groups	5
Rated current 40 A Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of light groups 4 Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Cooking group	1-phase (F)
Connector type Wieland GST18 Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 4 Number of light groups Number of groups 5 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of proups 5 Number of proups 5 Number of proups 4 Number of groups 4 Number of groups behind earth leakage switch Number of poles main switch No Number of poles main switch No Protection incoming RCD No Protection split load No Protection split load No Protection split load No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Main switch	40 A
Quantity and type of FI/LS switch Mounting method Surface mounted (plaster) Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of light groups 4 Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Rated current	40 A
Mounting methodSurface mounted (plaster)Degree of protection (IP)IP20Width in number of modular spacings24Depth110 mmExtension possibleYesHousing materialPlasticNumber of phases1LockableYesOver voltage protectionNoNumber of earth leakage switches 30 mA2With transparent coverNoProtectionMiniature- / earth leakage circuit breakerTotal number of groups5Number of direct groups4Number of groups behind earth leakage switch5Number of earth leakage circuit breakers5Number of earth leakage circuit breakersNoNumber of poles main switchNoNumber of poles main switch2Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways5Suitable for dataNoCooker groupSingle phase	Connector type	Wieland GST18
Degree of protection (IP) IP20 Width in number of modular spacings 24 Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of direct groups Number of groups 4 Number of groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways Suitable for data Cooker group Single phase	Quantity and type of FI/LS switch	
Width in number of modular spacings Depth	Mounting method	Surface mounted (plaster)
Depth 110 mm Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of light groups 4 Number of groups behind earth leakage switch Number of groups behind earth leakage switch Number of groups behind earth leakage switch Number of proups 4 Number of groups behind earth leakage 5 Suitch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Degree of protection (IP)	IP20
Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of direct groups Number of groups 4 Number of groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways Suitable for data No Cooker group Single phase		24
Extension possible Yes Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of direct groups Number of groups 4 Number of groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways Suitable for data No Cooker group Single phase	Depth	110 mm
Housing material Plastic Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	·	Yes
Number of phases 1 Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of earth leakage circuit breakers Number of of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	·	Plastic
Lockable Yes Over voltage protection No Number of earth leakage switches 30 mA 2 Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	_	1
Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Protection incoming RCD Protection high integrity No Protection dual RCD Number of outgoing ways Suitable for data No Cooker group No No No No No Single phase	·	Yes
Number of earth leakage switches 30 mA Number of earth leakage switches 300 mA With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Protection incoming RCD Protection high integrity No Protection dual RCD Number of outgoing ways Suitable for data No Cooker group No No No No No Single phase	Over voltage protection	No
Number of earth leakage switches 300 mA With transparent cover No Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	- '	2
With transparent cover Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of direct groups Number of light groups 4 Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase		
Protection Miniature- / earth leakage circuit breaker Total number of groups 5 Number of direct groups Number of light groups 4 Number of groups behind earth leakage 5 switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	-	No
Total number of groups Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch No Number of poles main switch Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways Suitable for data No Cooker group Single phase		Miniature- / earth leakage circuit breaker
Number of direct groups Number of light groups A Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch A No No Protection incoming RCD Protection high integrity No Protection dual RCD No No No No No No No No No N	Total number of groups	
Number of light groups Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Ad A Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways Suitable for data Cooker group Number of groups sehind earth leakage Solitable for data		
Number of groups behind earth leakage switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch Main switch rated current Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways Suitable for data Cooker group Single phase	- '	4
switch Number of earth leakage circuit breakers Number of arc fault detection devices AFDD Protection main switch Number of poles main switch Number of poles main switch Ad A Protection incoming RCD Protection high integrity No Protection split load Protection dual RCD Number of outgoing ways Suitable for data Cooker group Number of sarch leakage circuit breakers No No No Single phase		5
Number of arc fault detection devices AFDD Protection main switch No Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD No Number of outgoing ways 5 Suitable for data Cooker group No No No Single phase	J .	
Protection main switch Number of poles main switch 2 Main switch rated current 40 A Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD Number of outgoing ways Suitable for data Cooker group No No No Single phase	Number of earth leakage circuit breakers	
Number of poles main switch2Main switch rated current40 AProtection incoming RCDNoProtection high integrityNoProtection split loadNoProtection dual RCDNoNumber of outgoing ways5Suitable for dataNoCooker groupSingle phase	Number of arc fault detection devices AFDD	
Main switch rated current Protection incoming RCD No Protection high integrity No Protection split load No Protection dual RCD Number of outgoing ways Suitable for data Cooker group No No Single phase	Protection main switch	No
Protection incoming RCD Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group No No Single phase	Number of poles main switch	2
Protection high integrity Protection split load Protection dual RCD No Number of outgoing ways Suitable for data Cooker group No No Single phase	Main switch rated current	40 A
Protection split load No Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Protection incoming RCD	No
Protection dual RCD No Number of outgoing ways 5 Suitable for data No Cooker group Single phase	Protection high integrity	No
Number of outgoing ways5Suitable for dataNoCooker groupSingle phase	Protection split load	No
Suitable for data No Cooker group Single phase	Protection dual RCD	No
Cooker group Single phase	Number of outgoing ways	5
	Suitable for data	No
Cooker group suitable as power current group No	Cooker group	Single phase
	Cooker group suitable as power current group	No



With socket outlet	No
With bell transformer	No
Type of over voltage protection device	-
With meter	No
Built-in depth	

The group boxes for "pluggable installation" are equipped with an output bridge with (optional) Wieland GST18 or WAGO Winsta Midi connectors. The fully pre-wired pluggable output bridge can be fitted with a maximum of 9 to 13 connectors for 1-phase end groups. Connections for electric cooking, mechanical ventilation or power groups have also been taken into account: space has been reserved in the output bridge for a maximum of 2 to 4 pieces of 5-pole connectors. All connectors are pre-wired with 2.5 mm² and fitted with locking as standard. Almost all "traditional" group boxes can be equipped with a fully pre-wired pluggable output bridge with Wieland GST18 or WAGO Winsta Midi connectors. Just like the standard group boxes, the pluggable group boxes are also fully assembled by Attema within a few days according to your wishes. If you are looking for a different configuration, you can put together your own pluggable group box in no time at all.

