Click-mate NXT | Pluggable distribution boards



NXT MWA-23/23F/00-H2 groepenkast

| Article no: | AT91599 |
|--|--|
| EAN: | 8712259535456 |
| Width | 220 mm |
| Height | 390 mm |
| Number of groups (blue) | 3 |
| Number of groups (grey) | 4 |
| Number of earth fault switches 2P | 2 |
| Phases | 1-phase wired |
| Groups | 7 |
| Cooking group | 1-phase (F) |
| Main switch | 40 A |
| Rated current | 40 A |
| Connector type | WAGO Winsta Midi |
| Quantity and type of FI/LS switch | |
| Mounting method | Surface mounted (plaster) |
| Degree of protection (IP) | IP20 |
| Width in number of modular spacings | 24 |
| Depth | 110 mm |
| Extension possible | Yes |
| Housing material | Plastic |
| Number of phases | 1 |
| Lockable | Yes |
| Over voltage protection | No |
| Number of earth leakage switches 30 mA | 2 |
| Number of earth leakage switches 300 mA | |
| With transparent cover | No |
| Protection | Miniature- / earth leakage circuit breaker |
| Total number of groups | 7 |
| Number of direct groups | |
| Number of light groups | 6 |
| Number of groups behind earth leakage switch | 7 |
| Number of earth leakage circuit breakers | |
| Number of arc fault detection devices AFDD | |
| Protection main switch | No |
| Number of poles main switch | 2 |
| Main switch rated current | 40 A |
| Protection incoming RCD | No |
| Protection high integrity | No |
| Protection split load | No |
| Protection dual RCD | No |
| Number of outgoing ways | 7 |
| Suitable for data | No |
| Cooker group | Single phase |
| Cooker group suitable as power current group | No |



| With socket outlet | No |
|--|----|
| With bell transformer | No |
| Type of over voltage protection device | - |
| With meter | No |
| Built-in depth | |

The group boxes for "pluggable installation" are equipped with an output bridge with (optional) Wieland GST18 or WAGO Winsta Midi connectors. The fully pre-wired pluggable output bridge can be fitted with a maximum of 9 to 13 connectors for 1-phase end groups. Connections for electric cooking, mechanical ventilation or power groups have also been taken into account: space has been reserved in the output bridge for a maximum of 2 to 4 pieces of 5-pole connectors. All connectors are pre-wired with 2.5 mm² and fitted with locking as standard. Almost all "traditional" group boxes can be equipped with a fully pre-wired pluggable output bridge with Wieland GST18 or WAGO Winsta Midi connectors. Just like the standard group boxes, the pluggable group boxes are also fully assembled by Attema within a few days according to your wishes. If you are looking for a different configuration, you can put together your own pluggable group box in no time at all.

