

Click-mate NXT | Pluggable distribution boards



NXT MWI-23/23/22F-H4 groepenkast

Article no:	AT91613
EAN:	8712259535593
Width	220 mm
Height	390 mm
Number of groups (blue)	3
Number of groups (lightblue)	3
Number of groups (grey)	3
Number of earth fault switches 2P	3
Phases	3-phase wired
Groups	9
Cooking group	1-phase (F)
Main switch	40 A
Rated current	3 x 32 A
Connector type	Wieland GST18
Quantity and type of FI/LS switch	
Mounting method	Surface mounted (plaster)
Degree of protection (IP)	IP20
Width in number of modular spacings	24
Depth	110 mm
Extension possible	Yes
Housing material	Plastic
Number of phases	3
Lockable	Yes
Over voltage protection	No
Number of earth leakage switches 30 mA	3
Number of earth leakage switches 300 mA	
With transparent cover	No
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	9
Number of direct groups	
Number of light groups	8
Number of groups behind earth leakage switch	9
Number of earth leakage circuit breakers	
Number of arc fault detection devices AFDD	
Protection main switch	No
Number of poles main switch	4
Main switch rated current	40 A
Protection incoming RCD	No
Protection high integrity	No
Protection split load	No
Protection dual RCD	No
Number of outgoing ways	9
Suitable for data	No
Cooker group	Single phase

Cooker group suitable as power current group	No
With socket outlet	No
With bell transformer	No
Type of over voltage protection device	-
With meter	No
Built-in depth	

The group boxes for "pluggable installation" are equipped with an output bridge with (optional) Wieland GST18 or WAGO Winsta Midi connectors. The fully pre-wired pluggable output bridge can be fitted with a maximum of 9 to 13 connectors for 1-phase end groups. Connections for electric cooking, mechanical ventilation or power groups have also been taken into account: space has been reserved in the output bridge for a maximum of 2 to 4 pieces of 5-pole connectors. All connectors are pre-wired with 2.5 mm² and fitted with locking as standard. Almost all "traditional" group boxes can be equipped with a fully pre-wired pluggable output bridge with Wieland GST18 or WAGO Winsta Midi connectors. Just like the standard group boxes, the pluggable group boxes are also fully assembled by Attema within a few days according to your wishes. If you are looking for a different configuration, you can put together your own pluggable group box in no time at all.