

Click-mate NXT | Pluggable distribution boards



NXT LWI-24/23/23F-H4 groepenkast

Article no:	AT91619
EAN:	8712259535654
Width	330 mm
Height	390 mm
Number of groups (blue)	4
Number of groups (lightblue)	4
Number of groups (grey)	3
Number of earth fault switches 2P	3
Phases	3-phase wired
Groups	11
Cooking group	1-phase (F)
Main switch	40 A
Rated current	3 x 32 A
Connector type	Wieland GST18
Quantity and type of FI/LS switch	
Mounting method	Surface mounted (plaster)
Degree of protection (IP)	IP20
Width in number of modular spacings	36
Depth	110 mm
Extension possible	Yes
Housing material	Plastic
Number of phases	3
Lockable	Yes
Over voltage protection	No
Number of earth leakage switches 30 mA	3
Number of earth leakage switches 300 mA	
With transparent cover	No
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	11
Number of direct groups	
Number of light groups	10
Number of groups behind earth leakage switch	11
Number of earth leakage circuit breakers	
Number of arc fault detection devices AFDD	
Protection main switch	No
Number of poles main switch	4
Main switch rated current	40 A
Protection incoming RCD	No
Protection high integrity	No
Protection split load	No
Protection dual RCD	No
Number of outgoing ways	11
Suitable for data	No
Cooker group	Single phase

Cooker group suitable as power current group	No
With socket outlet	No
With bell transformer	No
Type of over voltage protection device	-
With meter	No
Built-in depth	

The group boxes for "pluggable installation" are equipped with an output bridge with (optional) Wieland GST18 or WAGO Winsta Midi connectors. The fully pre-wired pluggable output bridge can be fitted with a maximum of 9 to 13 connectors for 1-phase end groups. Connections for electric cooking, mechanical ventilation or power groups have also been taken into account: space has been reserved in the output bridge for a maximum of 2 to 4 pieces of 5-pole connectors. All connectors are pre-wired with 2.5 mm² and fitted with locking as standard. Almost all "traditional" group boxes can be equipped with a fully pre-wired pluggable output bridge with Wieland GST18 or WAGO Winsta Midi connectors. Just like the standard group boxes, the pluggable group boxes are also fully assembled by Attema within a few days according to your wishes. If you are looking for a different configuration, you can put together your own pluggable group box in no time at all.