

K40 Plinth System



ET40 simplex telephone connecting point white (RAL 9010)

- Consists of mounting plate with pre-mounted circuit board, cap, cover plate with dust cap and attachment hardware.
- Is suitable for analogue telephone connection via RJ11 plug or ISDN connection via RJ45 4-pin plug.
- Wiring is connected via screw terminal block with conductor protection.
- Can be used horizontally or vertically.
- Circuit board and cover plate can be rotated for vertical application.
- Overlap with skirting duct is 5 mm. It is unnecessary to cut the skirting duct cover perfectly square at exactly the right length.

Article no:	AT9209
EAN:	8712259254357
Colour	-
Amount Packaging	10 st.
Degree of protection (IP)	-
Material	Plastic
Halogen free	No
RAL-number	9010
Mounting direction	-
Anti-bacterial treatment	No
Impact strength	-
Decoration	None
Height baseboard duct	70 mm
Depth plinth skirting duct	24 mm
Number of device units	
Equipped with	Telephone connection
Mounting method installation unit	Standard
Dispatch	10

The K40 plinth system has a modern design and includes extremely compact switching devices that lend themselves to the installation of complete surface-mount systems for 230V, low-voltage and data cabling. K40 is easy to mount and install. Thanks to the symmetric cover strip, vertical applications are also possible. It is simple to expand and offers the flexibility of combination with the K25/P25 system. It can also be seamlessly integrated with existing systems. The system is extremely well suited for renovation and changing user requirements. The switching devices can easily be moved. The usable storage area for the wiring remains optimal.

- The K40 system complies with EN 50085-1 and EN 50085-2-1.
- K40 is suitable for installations 16A/250V~.
- Protection class: IP40 (EN 60529).
- Impact resistance: IK07 (EN 50102).
- Minimum temperature for storage and transport: 5 °C.
- Minimum temperature during installation and use: 5 °C.
- Maximum operating temperature: + 60 °C.
- Compartment 1: cross section 350 mm²; maximum number of cables: 2x Ø 10 mm or 1x Ø 13 mm.
- Compartment 2: cross section 640 mm²; maximum number of cables: 3x Ø 10 mm or 2x Ø 13 mm.