


K40 Plinth System

K40 Skirting duct cover white (RAL 9010)

- For use as skirting duct.
- Attachment to trunking base via click connection.



Article no:	AT9237
EAN:	8712259063140
Colour	-
Amount Packaging	10 lgt. x 2 m
Degree of protection (IP)	-
Material	Plastic
Height	70 mm
Length	2000 mm
Halogen free	No
RAL-number	9010
Impact strength	-
Depth	24 mm
Sealing lip cover	None
Decoration	None
With protective foil	No
With carpet border	No

The K40 plinth system has a modern design and includes extremely compact switching devices that lend themselves to the installation of complete surface-mount systems for 230V, low-voltage and data cabling. K40 is easy to mount and install. Thanks to the symmetric cover strip, vertical applications are also possible. It is simple to expand and offers the flexibility of combination with the K25/P25 system. It can also be seamlessly integrated with existing systems. The system is extremely well suited for renovation and changing user requirements. The switching devices can easily be moved. The usable storage area for the wiring remains optimal.

- The K40 system complies with EN 50085-1 and EN 50085-2-1.
- K40 is suitable for installations 16A/250V~.
- Protection class: IP40 (EN 60529).
- Impact resistance: IK07 (EN 50102).
- Minimum temperature for storage and transport: 5 °C.
- Minimum temperature during installation and use: 5 °C.
- Maximum operating temperature: + 60 °C.
- Compartment 1: cross section 350 mm²; maximum number of cables: 2x Ø 10 mm or 1x Ø 13 mm.
- Compartment 2: cross section 640 mm²; maximum number of cables: 3x Ø 10 mm or 2x Ø 13 mm.