


K40 Plinth System



AE40 Outer corner white (RAL 9010)

- Including basic hook for simple installation of skirting duct.
- Skirting duct can be sawn off at a right angle.
- Attachment of cap via click connection.
- Overlap with skirting duct is 5 mm. It is unnecessary to cut the skirting duct cover perfectly square at exactly the right length.

Article no:	AT9286
EAN:	8712259254678
Colour	-
Amount Packaging	20 st.
Degree of protection (IP)	-
Material	Plastic
Height	
Halogen free	Yes
RAL-number	9010
Model	Base unit and cover
Impact strength	-
Depth	
Sealing lip cover	None
Decoration	None
With carpet border	No
Angle	90 - 90 °
Dispatch	20

The K40 plinth system has a modern design and includes extremely compact switching devices that lend themselves to the installation of complete surface-mount systems for 230V, low-voltage and data cabling. K40 is easy to mount and install. Thanks to the symmetric cover strip, vertical applications are also possible. It is simple to expand and offers the flexibility of combination with the K25/P25 system. It can also be seamlessly integrated with existing systems. The system is extremely well suited for renovation and changing user requirements. The switching devices can easily be moved. The usable storage area for the wiring remains optimal.

- The K40 system complies with EN 50085-1 and EN 50085-2-1.
- K40 is suitable for installations 16A/250V~.
- Protection class: IP40 (EN 60529).
- Impact resistance: IK07 (EN 50102).
- Minimum temperature for storage and transport: 5 °C.
- Minimum temperature during installation and use: 5 °C.
- Maximum operating temperature: + 60 °C.
- Compartment 1: cross section 350 mm²; maximum number of cables: 2x Ø 10 mm or 1x Ø 13 mm.
- Compartment 2: cross section 640 mm²; maximum number of cables: 3x Ø 10 mm or 2x Ø 13 mm.