


## K40 Plinth System



### DR40 Data corner guide

- For radius protection  $R=25$  mm of data cables.
- Easy to fit in basic corner or outside corner AE40 and inside corner IE40.
- Suitable for max. 5 cables  $\varnothing 6.5$  mm.

<b>Article no:</b>	<b>AT9289</b>
EAN:	8712259254739
Amount Packaging	10 st.
Material	Plastic
Dispatch	10



The K40 plinth system has a modern design and includes extremely compact switching devices that lend themselves to the installation of complete surface-mount systems for 230V, low-voltage and data cabling. K40 is easy to mount and install. Thanks to the symmetric cover strip, vertical applications are also possible. It is simple to expand and offers the flexibility of combination with the K25/P25 system. It can also be seamlessly integrated with existing systems. The system is extremely well suited for renovation and changing user requirements. The switching devices can easily be moved. The usable storage area for the wiring remains optimal.

- The K40 system complies with EN 50085-1 and EN 50085-2-1.
- K40 is suitable for installations 16A/250V~.
- Protection class: IP40 (EN 60529).
- Impact resistance: IK07 (EN 50102).
- Minimum temperature for storage and transport: 5 °C.
- Minimum temperature during installation and use: 5 °C.
- Maximum operating temperature: + 60 °C.
- Compartment 1: cross section 350 mm<sup>2</sup>; maximum number of cables: 2x  $\varnothing 10$  mm or 1x  $\varnothing 13$  mm.
- Compartment 2: cross section 640 mm<sup>2</sup>; maximum number of cables: 3x  $\varnothing 10$  mm or 2x  $\varnothing 13$  mm.