

K40 Plinth System



T40 Tee/branch connector cream (RAL 1013)

- Consists of basic plate, mounting plate, cap and branch cap with insert.
- For vertical branching with K40 skirting duct, raceway P25, K25, Z25 or KK 25x22 in which the correct separation of both compartments is continued.
- Entry from the wall is possible via round break-outs in the base plate.
- Sufficient splice area under the cap.
- Overlap with skirting duct is 5 mm. It is unnecessary to cut the skirting duct cover perfectly square at exactly the right length.

Article no:	AT9293
EAN:	8712259254814
Colour	Cream (RAL 1013)
Amount Packaging	10 st.
Degree of protection (IP)	-
Material	Plastic
Halogen free	Yes
RAL-number	1013
Impact strength	-
Decoration	-
Height baseboard duct	70 mm
Depth plinth skirting duct	24 mm
With carpet border	No
Height duct connection	
Width duct connection	
Diameter tube	
Duct connection	Mini/maxi trunking
Branch off duct connection	-
Colour cover	-
Dispatch	10

The K40 plinth system has a modern design and includes extremely compact switching devices that lend themselves to the installation of complete surface-mount systems for 230V, low-voltage and data cabling. K40 is easy to mount and install. Thanks to the symmetric cover strip, vertical applications are also possible. It is simple to expand and offers the flexibility of combination with the K25/P25 system. It can also be seamlessly integrated with existing systems. The system is extremely well suited for renovation and changing user requirements. The switching devices can easily be moved. The usable storage area for the wiring remains optimal.

- The K40 system complies with EN 50085-1 and EN 50085-2-1.
- K40 is suitable for installations 16A/250V~.
- Protection class: IP40 (EN 60529).
- Impact resistance: IK07 (EN 50102).
- Minimum temperature for storage and transport: 5 °C.
- Minimum temperature during installation and use: 5 °C.
- Maximum operating temperature: + 60 °C.
- Compartment 1: cross section 350 mm²; maximum number of cables: 2x Ø 10 mm or 1x Ø 13 mm.
- Compartment 2: cross section 640 mm²; maximum number of cables: 3x Ø 10 mm or 2x Ø 13 mm.